LTL with past and two-way very-weak alternating automata

Paul Gastin and Denis Oddoux

LIAFA, Université Paris 7, 2, place Jussieu, F-75251 Paris Cedex 05
Fax: 49 711 7816 310 — {Paul.Gastin,Denis.Oddoux}@liafa.jussieu.fr

Abstract. It is crucial for a model checker using LTL as a specification language to have very efficient translation of LTL formulas to Büchi automata. Most such algorithms are based on a tableau construction. Recently, an implementation using very-weak alternating automata as an intermediary step proved to be dramatically faster than previous implementations based on the tableau construction. In this paper, we want to generalize this method to PLTL (LTL with past modalities). For this, we study two-way very-weak alternating automata (2VWAA). Our main result is an efficient translation of 2VWAA to generalized Büchi automata (GBA). Since we can easily transform a PLTL formula to an equivalent 2VWAA, this algorithm allows to use PLTL specifications with classical model checkers such as SPIN.

1 Introduction

Nowadays, computer systems (both hardware and software) play a central role in most human activities, including safety critical areas. It is therefore essential to improve their reliability. For this, we need to formally specify their expected behaviors. Choosing the specification language is a crucial factor for the overall validation process. We need a language that allows to express easily all desired properties. Moreover the specification language must be easily amenable to validation techniques such as model checking for instance.

Temporal logics [12, 1, 11] are among the most widely used specification languages, the most popular ones being branching time temporal logics (CTL, CTL*) and linear time temporal logic (LTL). These logics are based on pure future modalities, i.e., modalities that does not depend on what happened before the current time. Adding past modalities to LTL does not increase its expressive power [5, 2, 9] but PLTL (LTL with past modalities) is exponentially more succinct than LTL [8]. More important for practical purposes is the well-known fact that adding past modalities make some specifications easier or more natural [10]. In this paper, we focus our attention on PLTL.

The drawback of using past modalities is that the satisfiability problem or the model checking problem are harder to solve. Not harder from a theoretical point of view since the satisfiability problem and the model checking problem are PSPACE complete [14] regardless of whether we use past modalities or not, but harder from a practical point of view. Model checking algorithms for PLTL

have already been proposed [6, 13, 17] but few have been implemented and used in actual model checker. This is surprising since past modalities make specifications much easier, more natural and more succinct. We believe that the reason is the difficulty to build efficiently a Büchi automaton associated with a PLTL formula, which is a crucial step for a model checker using PLTL as a specification language. This is precisely the problem addressed in the present paper.

The easiest construction is the so-called *tableau* construction (see e.g. [6, 10, 14]) but a straightforward implementation, called declarative tableau, is highly inefficient. The reason is that it starts by constructing all possible atoms, which is usually exponential in the size of the formula. Implementations are based on incremental tableau. They construct only reachable states and apply some simplification techniques. An incremental tableau construction for PLTL [6] requires backtracking and is much harder to implement than for LTL [4].

Following the automata theoretic approach of [16], another technique to generate efficiently a generalized Büchi automaton (GBA) from an LTL formula is to use very-weak alternating automata (VWAA) as an intermediary step. As demonstrated in [3], this yields an implementation which is dramatically faster than those based on the tableau construction. In this paper, we develop the same technique for PLTL. Since we have to deal with past modalities we use two-way very-weak alternating automata (2VWAA). Two-way alternating automata (2AA) were already proposed for specification languages that are much more expressive than PLTL [15, 7] and a translation procedure from general 2AA to GBA is given in [7]. Since PLTL formulas are sufficient to specify most interesting properties and can be easily translated to 2VWAA, it is very important to develop an efficient translation procedure restricted to 2VWAA.

The main result of this paper is an efficient translation procedure of *progressing* 2VWAA to GBA. Starting from a *progressing* 2VWAA with n states, we construct a GBA with at most 2^n states. Since the translation from a PLTL formula φ gives a progressing 2VWAA with at most $|\varphi|+1$ states, we get for this formula a GBA with at most $2^{|\varphi|+1}$ states. As a comparison, the algorithm of [7] gives an automaton with $2^{O(|\varphi|^2)}$ states (recall that the specification language considered in [7] is much more expressive than PLTL).

2 Preliminaries: Past Linear Temporal Logic (PLTL)

Most temporal logics used in model-checking for specifying the properties of systems are pure future logics such as LTL or CTL for instance. Being able to use past modalities makes some specifications much easier and natural. For instance, specifying that a grant may be issued only upon requests is easy with past modalities (one simply writes $\mathsf{G}(\texttt{grant} \rightarrow \mathsf{Y}(\neg\texttt{grant}\,\mathsf{S}\,\texttt{request}))$) but much harder in LTL. It is known that past modalities do not add any expressive power [10] but PLTL can be exponentially more succinct than LTL [8]. This is why we are interested in working on PLTL formulae.

Definition 1 (syntax). *The set of* PLTL formulae *on the set of atomic propositions* AP *is defined by* $\varphi ::= \bot \mid p \mid \neg\varphi \mid \varphi \vee \varphi \mid \mathsf{X}\varphi \mid \mathsf{Y}\varphi \mid \varphi\,\mathsf{U}\,\varphi \mid \varphi\,\mathsf{S}\,\varphi$, *where*

$\bot$ *stands for* false *and* p *ranges over* AP. *An* LTL formula *is a PLTL formula that uses neither* Y *nor* S.

Let $\Sigma = 2^{\mathrm{AP}}$ and $\Sigma^\infty = \Sigma^+ \cup \Sigma^\omega$. For any word u in Σ^∞ let $|u| = n$ if $u \in \Sigma^n$ and $|u| = \omega$ otherwise. Note that we are dealing both with finite and infinite words. Dealing with finite words is known to cause additional difficulties in LTL compared to dealing with infinite words only. But those difficulties cannot be avoided when we use the past modalities of PLTL. Hence we decided to treat the case of finite words as well.

Definition 2 (semantics). *Let* $u = u_1 u_2 \dots$ *be a word in* Σ^∞, *let* φ *be a PLTL formula, and* i *be a positive integer with* $1 \leq i \leq |u|$. *The relation* $u, i \models \varphi$ *(*φ *holds at position* i*) is defined as follows:*

- $u, i \not\models \bot$,
- $u, i \models p$ *if* $p \in u_i$,
- $u, i \models \neg \varphi_1$ *if* $u, i \not\models \varphi_1$,
- $u, i \models \varphi_1 \vee \varphi_2$ *if* $u, i \models \varphi_1$ *or* $u, i \models \varphi_2$,
- $u, i \models \mathsf{X}\varphi_1$ *if* $i < |u|$ *and* $u, i+1 \models \varphi_1$,
- $u, i \models \mathsf{Y}\varphi_1$ *if* $i > 1$ *and* $u, i-1 \models \varphi_1$,
- $u, i \models \varphi_1 \,\mathsf{U}\, \varphi_2$ *if* $\exists i \leq j \leq |u|$ *s.t.* $u, j \models \varphi_2$ *and* $\forall i \leq k < j$, $u, k \models \varphi_1$.
- $u, i \models \varphi_1 \,\mathsf{S}\, \varphi_2$ *if* $\exists 1 \leq j \leq i$ *s.t.* $u, j \models \varphi_2$ *and* $\forall j < k \leq i$, $u, k \models \varphi_1$.

Let $\mathcal{L}(\varphi) = \{u \in \Sigma^\infty \mid u, 1 \models \varphi\}$

Only basic operators have been defined above. We will of course also use the dual operators $\top, \wedge, \widetilde{\mathsf{X}}, \widetilde{\mathsf{Y}}, \widetilde{\mathsf{U}}, \widetilde{\mathsf{S}}$. For instance, $\widetilde{\mathsf{X}}\varphi = \neg\mathsf{X}\neg\varphi$ and $\varphi_1 \,\widetilde{\mathsf{S}}\, \varphi_2 = \neg(\neg\varphi_1 \,\mathsf{S}\, \neg\varphi_2)$. Note that $\widetilde{\mathsf{X}}\varphi$ is not equivalent to $\mathsf{X}\varphi$ on finite words: we have instead $\widetilde{\mathsf{X}}\varphi = \neg\mathsf{X}\top \vee \mathsf{X}\varphi$.

A PLTL formula can be written in *negative normal form*, where negations are on predicates only. A formula in negative normal form uses $\bot$, $\top$, predicates in AP, their negations, and the operators $\vee$, X, U, Y, S and their dual operators. A PLTL formula in negative normal form that is neither a disjunction ($\vee$) nor a conjunction ($\wedge$) is called a *temporal formula*. Notice that transforming a formula in negative normal form does not change the number of temporal operators of the formula. From now on, we suppose that every PLTL formula is in negative normal form.

3 Two-way very-weak alternating automata (2VWAA)

One of the most well-known techniques used to translate an LTL formula to a Büchi automaton is the *tableau construction*, as explained in [4] for instance. The tableau construction works also for PLTL (see [8] for instance). However we have shown in [3] the efficiency brought by using a very-weak alternating automaton as an intermediate step in the translation of an LTL formula to a Büchi automaton. Here we follow the same technique for PLTL. Since PLTL contains past modalities, we use two-way alternating automata.

In this section, we define *two-way alternating automata* and we study some properties of their *very-weak* restriction.

Definition 3 (2AA). *A two-way alternating automaton (2AA) is a six-tuple* $\mathcal{A} = (Q, \Sigma, \delta, I, F, R)$ *where*
- Q *is the set of states,*
- Σ *is the alphabet,*
- $\delta : Q \to 2^{2^Q \times 2^\Sigma \times 2^Q}$ *is the transition function,*
- $I \subseteq 2^Q$ *gives the initial condition,*
- $F \subseteq Q$ *is the set of final states.*
- $R \subseteq Q$ *is the set of repeated states.*

Remark 4. A more classical way of defining 2AAs would use $I' \in \mathcal{B}^+(Q)$ and $\delta' : Q \times \Sigma \to \mathcal{B}^+(Q \times \{-1, 1\})$, where -1 and 1 indicate whether the head moves left or right. The more classical representation of the transition function would be given by:

$$\delta'(p, a) = \bigvee_{(X,\alpha,Z)\in\delta(p), a\in\alpha} \bigwedge_{q\in X} (q, -1) \wedge \bigwedge_{q\in Z} (q, 1).$$

Conversely we may obtain our definition from the classical one, essentially by taking the disjunctive normal form. Hence the two approaches are equivalent.

We chose the representation of Definition 3 for implementation purposes. It allows for more compact representations of the automata and for faster algorithms. Notice in particular that in the transition function we use 2^Σ instead of Σ, so that transitions that differ only by actions can be gathered. In practice, this usually reduces a lot the number of transitions. However the automaton still reads words in Σ^∞.

Runs of 2AAs are defined using the following notion of Q-forests.

Definition 5 (Q-forest). *A Q-forest over a word $u \in \Sigma^\infty$ is a labeled forest (V, E, σ, ν) where:*
- V *is the set of vertices,*
- $E \subseteq V \times V$ *is the set of edges,*
- $\sigma : V \to Q$ *is the state labeling function,*
- $\nu : V \to \mathbb{N}$ *is the position labeling function: it indicates the letter the automaton is reading; $\forall x \in V$, $0 \leq \nu(x) \leq |u| + 1$, and $\forall (x, y) \in E$, either $\nu(y) = \nu(x) + 1$ if $\mathcal{A}$ goes forward on u, or $\nu(y) = \nu(x) - 1$ if $\mathcal{A}$ goes backward on u.*

We shall use the following notations in the rest of the paper:
- *let $\lambda = (\sigma, \nu) : V \to Q \times \mathbb{N}$ be the labelling function,*
- *let $E(x) = \{y \in V \mid (x, y) \in E\}$ be the set of the sons of x,*
- *let $E^+(x) = \{y \in V \mid (x, y) \in E^+\}$ and let $E^*(x) = E^+(x) \cup \{x\}$,*
- *let $\overleftarrow{E}(x) = \{y \in E(x) \mid \nu(y) = \nu(x) - 1\}$ be the set of the left sons of x, and let $\overrightarrow{E}(x) = E(x) \setminus \overleftarrow{E}(x)$ be the set of the right sons of x,*
- *let $\text{left}(x) = E^*(\overleftarrow{E}(x)) \cup \{x\}$,*
- *let $[x, y] = \{z \in E^*(x) \mid y \in E^*(z)\}$, $]x, y[= \{z \in E^+(x) \mid y \in E^+(z)\}$, and we define in the same way $[x, y[$ and $]x, y]$.*

Definition 6 (run, accepting run, language).

1. *A run ρ of a 2AA $\mathcal{A}$ on a word $u = u_1 u_2 \cdots \in \Sigma^\infty$ is a Q-forest (V, E, σ, ν) over u such that:*
   - *the roots satisfy the initial condition:*
     if $\Gamma \subseteq V$ are the roots of the forest, then $\sigma(\Gamma) \in I$ and $\nu(\Gamma) \subseteq \{1\}$,
   - *the sons of any node satisfy the transition function:*
     $\forall x \in V$ if $\nu(x) = 0$ or $\nu(x) = |u| + 1$ then $E(x) = \emptyset$,
     otherwise $\exists \alpha \in 2^\Sigma$, $u_{\nu(x)} \in \alpha$ and $(\sigma(\overleftarrow{E}(x)), \alpha, \sigma(\overrightarrow{E}(x))) \in \delta(\sigma(x))$.
2. *A run ρ is* accepting *if:*
   - *$\forall x \in V$, $\nu(x) = 0$ or $\nu(x) = |u| + 1$ imply $\sigma(x) \in F$,*
   - *any infinite branch of ρ goes infinitely often through R (note that ρ may have infinite branches even if u is finite).*
3. *$\mathcal{L}(\mathcal{A})$ is the set of words on which there exists an accepting run of $\mathcal{A}$.*

It is possible to build a smaller Büchi automaton from a very-weak alternating automaton than from a general alternating automaton. This was used successfully in [3] in the translation from LTL to BA and yields a very efficient algorithm. We follow similar ideas in this paper hence we introduce two-way *very-weak* alternating automata.

Definition 7 (2VWAA). *A two-way very-weak alternating automaton is a 2AA where there exists a partial order $\preccurlyeq$ on Q such that $\forall p \in Q$, $\forall (\overleftarrow{X}, \alpha, \overrightarrow{X}) \in \delta(p)$, $\forall q \in \overleftarrow{X} \cup \overrightarrow{X}$, $q \preccurlyeq p$.*

As explained already, our translation of PLTL formulas to Büchi automaton uses 2VWAA as an intermediate step. Actually, we use *progressing (or loop-free)* 2VWAA for which we describe in Section 5 an efficient translation to Büchi automaton.

Definition 8 (progressing runs and loops).

1. *A run ρ is* progressing *if any infinite branch $x_0 \dots x_n \dots$ in ρ satisfies the following property: $\forall N \geq 0$, $\exists i \geq 0$ $\nu(x_i) \geq N$.*
2. *A run ρ has a* loop *if two nodes on a same branch have the same label: $\exists x \in V$, $\exists y \in E^+(x)$, $\lambda(x) = \lambda(y)$. Otherwise ρ is* loop-free.
3. *A 2AA is* progressing *(respectively* loop-free*) if all runs (accepting or not) of this automaton are progressing (respectively* loop-free*).*

Note that a loop-free run on a finite word has no infinite branches and is therefore progressing. More generally, we have

Proposition 9. *Any loop-free run is progressing.*

Proof. Let ρ be a non progressing run: there exist an infinite branch $x_0 \dots x_n \dots$ and $N \geq 0$ such that $\forall i \geq 0$, $\nu(x_i) < N$. The set $\{\lambda(x_i) \mid i \geq 0\}$ is contained in $Q \times \{0, \dots, N\}$ which is finite. Hence there are infinitely many nodes with the same label on this infinite branch, and ρ has a loop. □

The converse of Proposition 9 is trivially false. Still, we have

Proposition 10. *A 2AA is progressing iff it is loop-free.*

Proof. Let $\mathcal{A}$ be a progressing 2AA and let ρ_0 be a run of $\mathcal{A}$ with a loop on a word u: there exist two nodes $x_0 \in V$ and $x_1 \in E^+(x)$ such that $\lambda(x_1) = \lambda(x_0)$. Now replace the subtree of x_1 by a copy of the subtree of x_0: we obtain a new run ρ_1 of $\mathcal{A}$ on u, with the nodes x_0, x_1, and a new node x_2 which is the copy of x_1 (and has the same label). We can repeat the previous step, replacing the subtree of x_2 by a copy of the subtree of x_0, obtaining a new run ρ_2 of $\mathcal{A}$ on u. Repeating this operation over and over again builds a sequence $(\rho_n)_{n\geq 0}$ of runs of $\mathcal{A}$ on u. ρ_n and ρ_{n+1} are identical until the depth of x_{n+1}, which is strictly increasing with n. Therefore, this sequence has a limit ρ which is still a run of $\mathcal{A}$ on u, and contains an infinite branch going through $x_0 \dots x_n \dots$ on which ν has an upper bound. This is a contradiction since any run of $\mathcal{A}$ is progressing. □

The next theorem shows that progressing 2VWAA have the same expressive power as general 2VWAA. It is important since, when combined with the translation of progressing 2VWAA to GBA presented in Section 5, it yields an efficient translation from general 2VWAA to GBA. However, from a PLTL formula, we directly build in Section 4 a *progressing* 2VWAA and the following theorem is not needed for translating PLTL formulas to GBA.

Theorem 11 (2VWAA to progressing 2VWAA). *Given a 2VWAA with n states we can effectively construct a progressing 2VWAA with at most $2n$ states, accepting the same language.*

Proof. Let $\mathcal{A} = (Q, \Sigma, \delta, I, F, R)$ be a 2VWAA, and let $\mathcal{A}' = (Q', \Sigma, \delta', I, F', R')$ be defined by:

- $Q' = Q \cup \overline{Q}$ where $\overline{Q} = \{\overline{q} \mid q \in Q\}$ is a copy of Q,
- δ' is defined as follows.
  - If $p \in Q$ then $\delta'(p) = \{(X, \alpha, Y[\overline{p}/p] \mid (X, \alpha, Y) \in \delta(p)\}$ where $Y[q/p] = Y$ if $p \notin Y$ and $Y[q/p] = Y \setminus \{p\} \cup \{q\}$ otherwise.
  - If $\overline{p} \in \overline{Q}$ then $\delta'(\overline{p}) = \{(X, \alpha, Y[\overline{p}/p] \mid (X, \alpha, Y) \in \delta(p) \wedge p \notin X\}$ if $p \notin R$, and $\delta'(\overline{p}) = \{(X \setminus \{p\}, \alpha, Y[\overline{p}/p] \mid (X, \alpha, Y) \in \delta(p)\}$ if $p \in R$.
- $F' = F \cup \overline{F}$, $R' = \overline{R}$.

We shall now prove in Lemmas 12 to 15 that $\mathcal{A}'$ is a progressing 2VWAA and accepts the same language as $\mathcal{A}$.

Lemma 12. *$\mathcal{A}'$ is a progressing 2VWAA.*

Proof. $\mathcal{A}$ is very-weak so it defines a partial order $\leq$ on Q. Let us consider the relation $\prec$ on Q' defined by:

- $\forall p \in Q$, $\overline{p} \prec p$,
- $\forall p < q \in Q$, $p \prec \overline{q}$.

The transitive and reflexive closure $\preccurlyeq$ of this relation is a partial order on Q'. With this partial order it is easy to show that $\mathcal{A}'$ is a 2VWAA.

Suppose there exists a non progressing run $\rho = (V, E, \sigma, \nu)$ of $\mathcal{A}'$ on a word u. From proposition 9 ρ has a loop, and there exist $x \in V$ and $y \in E^+(x)$ such

that $\lambda(x) = \lambda(y)$. Since $\mathcal{A}'$ is very-weak, we can find $x' \in V$ and $y' \in E(E(x'))$ such that $\lambda(x') = \lambda(y')$: either $y' \in \overleftarrow{E}(\overrightarrow{E}(x'))$ or $y' \in \overrightarrow{E}(\overleftarrow{E}(x'))$. The definition of δ' implies that no node of ρ state-labelled in Q [resp. $\overline{Q}$] can have a right [resp. left] son with the same state-label. This implies that $\sigma(y') \prec \sigma(x')$ which is a contradiction. Every run of $\mathcal{A}'$ is progressing so $\mathcal{A}'$ is progressing. □

Lemma 13. *From any accepting run of $\mathcal{A}$ we can build another accepting run $\rho = (V, E, \sigma, \nu)$ of $\mathcal{A}$ on the same word such that there is no pair x, y with $y \in E^+(x)$, $\sigma(x) \notin R$ and $\lambda(y) = \lambda(x)$.*

Proof. Let $\rho_0 = (V_0, E_0, \sigma, \nu)$ be an accepting run of $\mathcal{A}$ on a word u. We shall now build inductively a sequence $(\rho_n)_{n\geq 0}$ of runs as follows: for every $n \geq 0$, given a run $\rho_n = (V_n, E_n, \sigma, \nu)$ of $\mathcal{A}$ on u, for every node x of depth n in ρ_n, if $\sigma(x) \notin R$ and $\exists y \in E_n^+(x)$ such that $\lambda(y) = \lambda(x)$, we can find $x' \in E_n^+(x)$ such that $\lambda(x') = \lambda(x)$ and $\forall y \in E_n^+(x')$, $\lambda(y) \neq \lambda(x)$. Such a x' exists otherwise there would be an infinite branch of ρ ultimately state-labelled by $\sigma(x) \notin R$. Replace the sons of x with the sons of x'. We obtain this way a new run ρ_{n+1} of $\mathcal{A}$ on u, which is still accepting. Since every run ρ_n is identical to ρ_{n+1} up to depth n, the sequence $(\rho_n)_{n\geq 0}$ converges to a forest $\rho = (V, E, \sigma, \nu)$ which is still a run of $\mathcal{A}$ on u. Note that in ρ, there is no pair $x, y \in E^+(x)$ such that $\sigma(x) \notin R$ and $\lambda(y) = \lambda(x)$.

We shall now prove that ρ is accepting. Any node in ρ has the same label as a node in ρ_0, so $\nu(x) \in \{0, |u| + 1\} \Rightarrow \sigma(x) \in F$. Let $x_0, x_1, \ldots$ be an infinite branch of ρ. By construction, $\forall i \geq 0$, $x_i \in V_0$ and $x_{i+1} \in E_0^+(x_i)$ (every run ρ_{n+1} is built from ρ_n by connecting some nodes to an ancestor of their father). Therefore there exists an infinite branch in ρ_0 going through $x_0, x_1, \ldots$. Since $\mathcal{A}$ is very-weak and ρ_0 is accepting, the sequence $(\sigma(x_i))_{i\geq 0}$ is ultimately constant with a limit in R. Hence ρ is accepting. □

Lemma 14. $\mathcal{L}(\mathcal{A}) \subseteq \mathcal{L}(\mathcal{A}')$.

Proof. Let $\rho = (V, E, \sigma, \nu)$ be an accepting run of $\mathcal{A}$ on a word u. From lemma 13 we may assume that there is no pair x, y with $y \in E^+(x)$, $\sigma(x) \notin R$ and $\lambda(y) = \lambda(x)$. Now we intend to build an accepting run $\rho' = (V', E', \sigma', \nu')$ of $\mathcal{A}'$ on u. First we define σ' on V by $\sigma'(y) = \overline{\sigma(y)}$ if $\exists x \in V$ such that $y \in \overrightarrow{E}(x)$ and $\sigma(x) = \sigma(y)$ (if y is the right son of a node with the same state-label), and let $\sigma'(y) = \sigma(y)$ otherwise. Then we define $V' \subseteq V$ as follows: $\forall x \in V$, $\forall y \in \overleftarrow{E}(x)$ such that $\sigma'(x) = \overline{\sigma(y)}$, we remove from V all nodes in $E^*(y)$. Finally let E' and ν' be the restrictions of E and ν to V'.

Let us show first that ρ' is a run of $\mathcal{A}'$ on u: the roots Γ of ρ are also the roots of ρ', so $\sigma'(\Gamma) = \sigma(\Gamma) \in I$. Now let $x \in V'$ such that $1 \leq \nu(x) \leq |u|$. We shall prove that $\exists \alpha \in 2^\Sigma$, $u_{\nu'(x)} \in \alpha$ and $(\sigma'(\overleftarrow{E'}(x)), \alpha, \sigma'(\overrightarrow{E'}(x))) \in \delta'(\sigma'(x))$. First case: if $\sigma'(x) = \overline{p} \in \overline{Q}$ and $\exists y \in \overleftarrow{E}(x)$ with $\sigma(y) = p$, by construction of ρ', $p \in R$, $E'(x) = E(x)\backslash\{y\}$, and $\forall z \in E'(x)$, $\sigma'(z) = \overline{p}$ if $z \in \overrightarrow{E}(x)$ and $\sigma(z) = p$, and $\sigma'(z) = \sigma(z)$ otherwise. Since $\exists \alpha \in 2^\Sigma$, $u_{\nu(x)} \in \alpha$ and $(\sigma(\overleftarrow{E}(x)), \alpha, \sigma(\overrightarrow{E}(x))) \in \delta(\sigma(x))$, we deduce that $\exists \alpha \in 2^\Sigma$, $u_{\nu'(x)} \in \alpha$ and

$(\sigma'(\overleftarrow{E'}(x)), \alpha, \sigma'(\overrightarrow{E'}(x))) \in \delta'(\sigma'(x))$. The other cases are simpler and left to the reader.

Finally, we show that ρ' is accepting: from the construction of ρ', $\forall x \in V'$, $x \in V$, $\sigma'(x) = \sigma(x)$ or $\sigma'(x) = \overline{\sigma(x)}$ and $\nu'(x) = \nu(x)$. Hence $\nu'(x) \in \{0, |u| + 1|\} \Rightarrow \sigma'(x) \in F' = F \cup \overline{F}$. Since $\mathcal{A}'$ is very-weak, each infinite branch of ρ' is ultimately labelled by some state $q \in Q \cup \overline{Q}$. Since $\mathcal{A}'$ is progressing, this branch ultimately goes to the right only. Therefore $q = \overline{p} \in \overline{Q}$. Moreover, all the nodes of this branch also appear in the same order in an infinite branch of ρ, and are labelled by p in ρ. Hence $p \in R$ and $q \in R' = \overline{R}$. ρ' is accepting. □

Lemma 15. $\mathcal{L}(\mathcal{A}') \subseteq \mathcal{L}(\mathcal{A})$

Proof. Let $\rho' = (V', E', \sigma', \nu)$ be an accepting run of $\mathcal{A}'$ on a word u. For any node $x \in V'$ such that $\sigma'(x) = p$ or $\sigma'(x) = \overline{p}$ for some $p \in Q$, let $\sigma_0(x) = p$. Take $x \in V'$ such that $1 \leq \nu(x) \leq |u|$, and suppose that $\forall \alpha \in 2^\Sigma$ such that $u_{\nu(x)} \in \alpha$, $(\sigma_0(\overleftarrow{E'}(x)), \alpha, \sigma_0(\overrightarrow{E'}(x))) \notin \delta(\sigma_0(x))$, then necessarily $\sigma'(x) = \overline{p}$ for some $p \in R$ and $\exists \alpha \in 2^\Sigma$, $u_{\nu(x)} \in \alpha$ and $(\sigma_0(\overleftarrow{E'}(x)) \cup \{p\}, \alpha, \sigma_0(\overrightarrow{E'}(x))) \in \delta(\sigma_0(x))$. Note also that $x \in \overrightarrow{E'}$ for some x' such that $\sigma_0(x') = p$. Now add to x a new son labelled $(\sigma_0(x), \nu(x) - 1)$ and marked. Doing this for all such x builds a new forest ρ_0, for which all unmarked nodes satisfy the requirements of the definition of a run.

For every $n \geq 0$, given a forest ρ_n, replace any marked node of depth n with a copy of the subtree of its grandfather. (Note that this creates new marked nodes at depth $n + 2$). This creates a new forest ρ_{n+1} and in this construction, $\forall n \geq 0$, all unmarked nodes in ρ_n satisfy the requirements of the definition of a run, and there are no marked nodes up to depth $n - 1$. Since every run ρ_n is identical to ρ_{n+1} up to the depth $n - 1$, the sequence $(\rho_n)_{n \geq 0}$ converges to a forest $\rho = (V, E, \sigma, \nu)$.

The roots of ρ are the roots of ρ' and satisfy the initial condition. ρ does not contain any marked node so ρ is a run of $\mathcal{A}$ on u.

For all $x \in V$, $\nu(x) \in \{0, |u| + 1\}$ implies $\sigma(x) \in F$. Let $x_0, x_1, \ldots$ be an infinite branch of ρ. Either there exists $N \geq 0$ such that for all $n \geq N$, x_n is not marked in ρ_n. Then, $x_0, x_1, \ldots$ is a branch of ρ_N. Hence, it ends like a branch of ρ_0, and is ultimately state-labelled in R. Otherwise, for all $N \geq 0$, there exists $n \geq N$ such that x_n is marked in ρ_n. Any marked node is state-labelled by an element of R, and $\mathcal{A}$ is very-weak so this branch is ultimately state-labelled by some $p \in R$. Hence ρ is accepting. □

4 PLTL to progressing 2VWAA

This section is devoted to the first step of our algorithm: from a PLTL formula with n temporal operators we can compute a progressing 2VWAA with at most $n + 1$ states. We first define notations that simplify the definition of the automaton, then we give the construction and sketch its proof.

Definition 16 (notations).

1. *For* $J_1, J_2 \in 2^{2^Q \times 2^\Sigma \times 2^Q}$ *we define* $J_1 \otimes J_2 = \{(\overleftarrow{X}_1 \cup \overleftarrow{X}_2, \alpha_1 \cap \alpha_2, \overrightarrow{X}_1 \cup \overrightarrow{X}_2) \mid (\overleftarrow{X}_1, \alpha_1, \overrightarrow{X}_1) \in J_1$ *and* $(\overleftarrow{X}_2, \alpha_2, \overrightarrow{X}_2) \in J_2\}$,
2. *For a PLTL formula* ψ *in negative normal form we define* $\overline{\psi}$ *inductively by:*
   - $\overline{\psi_1 \vee \psi_2} = \overline{\psi_1} \cup \overline{\psi_2}$,
   - $\overline{\psi_1 \wedge \psi_2} = \{X_1 \cup X_2 \mid X_1 \in \overline{\psi_1}$ *and* $X_2 \in \overline{\psi_2}\}$, *and*
   - $\overline{\psi} = \{\{\psi\}\}$ *if* ψ *is a temporal formula.*

It is actually not completely immediate to deal smoothly with the special cases raised when checking a past modality at the beginning of a word, or a future modality at the end of a finite word. We solve this problem using a special state END, which is reached in an accepting run when the current position ν is outside the word u ($\sigma(x) = \text{END} \Rightarrow \nu(x) = 0$ or $\nu(x) = |u| + 1$).

Definition 17 (φ to $\mathcal{A}_\varphi$). *For any PLTL formula* φ *in negative normal form on the set* AP, *let* $\mathcal{A}_\varphi = (Q, \Sigma, \delta, I, F, R)$ *be the 2AA defined by:*

- $Q = sub(\varphi) \cup \{\text{END}\}$ *where* $sub(\varphi)$ *are the temporal subformulae of* φ,
- $\Sigma = 2^{\text{AP}}$,
- $I = \overline{\varphi}$,
- $F = \{\text{END}\}$,
- R *is the set of the subformulae in* $sub(\varphi)$ *that are not of the form* $\varphi_1 \,\mathsf{U}\, \varphi_2$,
- δ *is defined below (*Δ *extends* δ *to* $\mathcal{B}^+(Q)$*):*

$$\begin{cases} \delta(\bot) = \emptyset \\ \delta(\top) = \{(\emptyset, \Sigma, \emptyset)\} \\ \delta(p) = \{(\emptyset, \Sigma_p, \emptyset)\} \text{ where } \Sigma_p = \{a \in \Sigma \mid p \in a\} \\ \delta(\neg p) = \{(\emptyset, \Sigma_{\neg p}, \emptyset)\} \text{ where } \Sigma_{\neg p} = \Sigma \backslash \Sigma_p \\ \delta(\mathsf{X}\psi) = \{(\emptyset, \Sigma, e) \mid e \in \overline{\psi}\} \\ \delta(\widetilde{\mathsf{X}}\psi) = \{(\emptyset, \Sigma, e) \mid e \in \overline{\psi}\} \cup \{(\emptyset, \Sigma, \{\text{END}\})\} \\ \delta(\mathsf{Y}\psi) = \{(e, \Sigma, \emptyset) \mid e \in \overline{\psi}\} \\ \delta(\widetilde{\mathsf{Y}}\psi) = \{(e, \Sigma, \emptyset) \mid e \in \overline{\psi}\} \cup \{(\{\text{END}\}, \Sigma, \emptyset)\} \\ \delta(\psi_1 \,\mathsf{U}\, \psi_2) = \Delta(\psi_2) \ \cup (\Delta(\psi_1) \otimes \{(\emptyset, \Sigma, \{\psi_1 \,\mathsf{U}\, \psi_2\})\}) \\ \delta(\psi_1 \,\widetilde{\mathsf{U}}\, \psi_2) = \Delta(\psi_2) \ \otimes (\Delta(\psi_1) \cup \{(\emptyset, \Sigma, \{\psi_1 \,\widetilde{\mathsf{U}}\, \psi_2\}), (\emptyset, \Sigma, \{\text{END}\})\}) \\ \delta(\psi_1 \,\mathsf{S}\, \psi_2) = \Delta(\psi_2) \ \cup (\Delta(\psi_1) \otimes \{(\{\psi_1 \,\mathsf{S}\, \psi_2\}, \Sigma, \emptyset)\}) \\ \delta(\psi_1 \,\widetilde{\mathsf{S}}\, \psi_2) = \Delta(\psi_2) \ \otimes (\Delta(\psi_1) \cup \{(\{\psi_1 \,\widetilde{\mathsf{S}}\, \psi_2\}, \Sigma, \emptyset), (\{\text{END}\}, \Sigma, \emptyset)\}) \\ \delta(\text{END}) = \emptyset \end{cases}$$

$$\begin{cases} \Delta(\psi) = \delta(\psi) \text{ if } \psi \text{ is a temporal formula} \\ \Delta(\psi_1 \vee \psi_2) = \Delta(\psi_1) \cup \Delta(\psi_2) \\ \Delta(\psi_1 \wedge \psi_2) = \Delta(\psi_1) \otimes \Delta(\psi_2) \end{cases}$$

Theorem 18 (PLTL to progressing 2VWAA). *For any PLTL formula in negative normal form* φ *with* n *temporal subformulae, the automaton* $\mathcal{A}_\varphi$ *is a progressing 2VWAA with at most* $n + 1$ *states and* $\mathcal{L}(\mathcal{A}_\varphi) = \mathcal{L}(\varphi)$.

Proof. Let us define $\psi_1 \preccurlyeq \psi_2$ if $\psi_1 = \text{END}$ or if ψ_1 is a subformula of ψ_2. It is easy to see with this partial order that $\mathcal{A}_\varphi$ is very-weak.

Now, we show that $\mathcal{A}_\varphi$ is progressing. Suppose that a node x and its son y have the same state-label ψ in a run of $\mathcal{A}_\varphi$. Then, either ($y \in \overrightarrow{E}(x)$ and ($\psi = \psi_1 \,\mathsf{U}\, \psi_2$ or $\psi = \psi_1 \,\widetilde{\mathsf{U}}\, \psi_2$)), or ($y \in \overleftarrow{E}(x)$ and ($\psi = \psi_1 \,\mathsf{S}\, \psi_2$ or $\psi = \psi_1 \,\widetilde{\mathsf{S}}\, \psi_2$)).

Now let $x_0, x_1, \ldots$ be an infinite branch of a run ρ of $\mathcal{A}_\varphi$. Since $\mathcal{A}_\varphi$ is very-weak, the sequence $\sigma(x_0), \sigma(x_1), \ldots$ is ultimately constant. From the previous statement, necessarily the limit of this sequence is a formula $\psi_1 \,\mathsf{U}\, \psi_2$ or $\psi_1 \,\widetilde{\mathsf{U}}\, \psi_2$, and hence ν is strictly increasing from a certain node on the branch: $\mathcal{A}_\varphi$ is progressing.

The proof for $\mathcal{L}(\mathcal{A}_\varphi) = \mathcal{L}(\varphi)$ is omitted. It is similar to the classical proof used for the similar translation of LTL formulas to VWAA. □

5 Progressing 2VWAA to GBA

The general translation from a 2AA to a BA is rather involved. Here we take full advantage of the fact that we start from a progressing 2VWAA. The basic idea, starting from an accepting run ρ of a 2AA $\mathcal{A}$ over a word $u = u_1 u_2 \ldots \in \Sigma^\infty$, is to consider the sets $X_i = \sigma(\nu^{-1}(i))$, and to build a kind of automaton $\mathcal{B}$ such that the sequence $X_0, X_1, X_2, \ldots$ is an accepting run of $\mathcal{B}$ on u. Transitions of $\mathcal{B}$ should reflect the fact that each node x of ρ satisfies the transition function of $\mathcal{A}$. If $\nu(x) = i$, this involves the sets X_{i-1}, X_i, X_{i+1} and the letter u_i. Hence it is natural to consider quadruples $(X_{i-1}, X_i, X_{i+1}, u_i)$ as transitions of $\mathcal{B}$. This is why we introduce here *generalized* BA having such quadruples as transitions. We are also using several acceptance conditions on transitions instead of states since the construction becomes simpler.

Definition 19 (GBA). *A GBA is a five-tuple $\mathcal{G} = (Q, \Sigma, T, I, F, \mathcal{T})$ where:*
- *Q is the set of states,*
- *Σ is the alphabet,*
- *$T \subseteq Q \times Q \times Q \times 2^\Sigma$ is the transition function,*
- *$I \subseteq Q \times Q$ is the set of initial states,*
- *$F \subseteq Q \times Q$ is the set of final states,*
- *$\mathcal{T} = \{T_1, \ldots, T_r\}$ where $T_j \subseteq T$ are the acceptance tables.*

Definition 20 (run, accepting run, language).
1. *A* run *σ of a GBA $\mathcal{G}$ on a word $u = u_1 u_2 \ldots \in \Sigma^\infty$ is*
   - *a sequence $q_0, q_1, \alpha_1, \ldots, q_n, \alpha_n, q_{n+1}$ if $u \in \Sigma^n$ for some $n \in \mathbb{N}^*$ or,*
   - *a sequence $q_0, q_1, \alpha_1, \ldots, q_n, \alpha_n, \ldots$ if $u \in \Sigma^\omega$,*

   such that $(q_0, q_1) \in I$, and $\forall 1 \leq i \leq |u|$, $u_i \in \alpha_i$ and $(q_{i-1}, q_i, q_{i+1}, \alpha_i) \in T$.
2. *A run σ is* accepting *if $u \in \Sigma^n$ and $(q_n, q_{n+1}) \in F$ or $u \in \Sigma^\omega$ and σ uses infinitely many transitions from each T_j, $1 \leq j \leq r$.*
3. *$\mathcal{L}(\mathcal{G})$ is the set of words on which there exists an accepting run of $\mathcal{G}$.*

Definition 21 ($\mathcal{A}$ to $\mathcal{G}^1_\mathcal{A}$). *For any progressing 2VWAA $\mathcal{A} = (Q, \Sigma, \delta, I, F, R)$, let $\mathcal{G}^1_\mathcal{A} = (Q', \Sigma, T', I', F', \mathcal{T}')$ be the GBA defined by:*
- *$Q' = 2^Q$,*

– $T' = \{(\overleftarrow{X}, X, \overrightarrow{X}, \alpha) \mid \exists\ (\overleftarrow{Y}, \alpha, \overrightarrow{Y}) \in \bigotimes_{q \in X} \delta(q)$ *with* $\overleftarrow{Y} \subseteq \overleftarrow{X}$ *and* $\overrightarrow{Y} \subseteq \overrightarrow{X}\}$,
– $I' = \{(X, Y) \in Q' \times Q' \mid X \subseteq F$ *and* $\exists Z \in I$ *with* $Z \subseteq Y\}$,
– $F' = \{(X, Y) \in Q' \times Q' \mid Y \subseteq F\}$,
– $\mathcal{T}' = \{T'_q \mid q \in Q \backslash R\}$ *where*
$T'_q = \{(\overleftarrow{X}, X, \overrightarrow{X}, \alpha) \in T' \mid q \notin X$ *or*
$\exists (\overleftarrow{Y}, \beta, \overrightarrow{Y}) \in \delta(q)$ *with* $\overleftarrow{Y} \subseteq \overleftarrow{X}$, $\overrightarrow{Y} \subseteq \overrightarrow{X}$, $\beta \supseteq \alpha$ *and* $q \notin \overrightarrow{Y}\}$

Indeed, the hard part in a translation from a 2AA $\mathcal{A}$ to a GBA $\mathcal{G}$ is to make sure that each accepting run of $\mathcal{G}$, which is a *flat* sequence of nodes, can be lifted to a Q-forest which defines an accepting run of $\mathcal{A}$. It is remarkable that if $\mathcal{A}$ is a progressing 2VWAA, we can simply use sequences $X_0, X_1, X_2, \ldots$ as runs of $\mathcal{G}$ and still be able to lift them to accepting runs of $\mathcal{A}$.

Proposition 22. *For any progressing 2VWAA* $\mathcal{A}$, $\mathcal{L}(\mathcal{G}^1_{\mathcal{A}}) \subseteq \mathcal{L}(\mathcal{A})$.

Actually $\mathcal{L}(\mathcal{G}^1_{\mathcal{A}}) = \mathcal{L}(\mathcal{A})$, but the other inclusion follows directly from results that will be proved afterwards, hence we will not prove it here. See theorem 27 for the final result.

Proof. Let $X_0, X_1, \alpha_1, X_2, \alpha_2, \ldots$ be an accepting run of $\mathcal{G}^1_{\mathcal{A}}$ on a word $u = u_1 u_2 \ldots \in \Sigma^\infty$. We are going to define a labelled graph $\rho = (V, E, \sigma, \nu)$. Let $V = \{(q, i) \mid i \geq 0,\ q \in X_i\}$. By definition of T', $\forall 1 \leq i \leq |u|$, $\forall q \in X_i$, there exist $\overleftarrow{Y} \subseteq X_{i-1}$, $\overrightarrow{Y} \subseteq X_{i+1}$ and $\alpha \in 2^\Sigma$ with $\alpha_i \subseteq \alpha$ and $(\overleftarrow{Y}, \alpha, \overrightarrow{Y}) \in \delta(q)$, and such that $q \notin \overrightarrow{Y}$ whenever $q \notin R$ and $(X_{i-1}, X_i, X_{i+1}, \alpha_i) \in T'_q$. Let $E((q, i)) = \overleftarrow{Y} \times \{i-1\} \cup \overrightarrow{Y} \times \{i+1\}$. If $i \in \{0, |u|+1\}$ then let $E((q, i)) = \emptyset$. $\forall (q, i) \in V$, let $\sigma((q, i)) = q$ and $\nu((q, i)) = i$.

Since $(X_0, X_1) \in I'$, $\exists \Gamma \subseteq X_1 \times \{1\}$ such that $\sigma(\Gamma) \in I$. Now if we "unfold" the labelled graph $\rho = (V, E, \sigma, \nu)$ from the set of roots Γ, we obtain a Q-forest $\rho' = (V', E', \sigma', \nu')$.

Let $x \in V'$. If $\nu'(x) \in \{0, |u|+1\}$ then $E'(x) = \emptyset$. Otherwise, let $q = \sigma'(x)$ and $i = \nu'(x)$, let $\overleftarrow{Y} = \sigma'(\overleftarrow{E'}(x)) = \sigma(E(q, i) \cap Q \times \{i-1\})$ and $\overrightarrow{Y} = \sigma'(\overrightarrow{E'}(x)) = \sigma(E(q, i) \cap Q \times \{i+1\})$. By construction of ρ there exists $\alpha \in 2^\Sigma$ with $\alpha_i \subseteq \alpha$ and $(\overleftarrow{Y}, \alpha, \overrightarrow{Y}) \in \delta(q)$. Since $u_i \in \alpha_i$, we have proved that the sons of x satisfy the transition function. Hence ρ' is a run of $\mathcal{A}$ on u.

We shall now check that ρ' is accepting:
– $\sigma'(\nu'^{-1}(0)) \subseteq \sigma(\nu^{-1}(0)) = X_0 \subseteq F$, since $(X_0, X_1) \in I'$,
– if u is finite of length n then $\sigma'(\nu'^{-1}(n+1)) \subseteq \sigma(\nu^{-1}(n+1)) = X_{n+1} \subseteq F$ since $(X_n, X_{n+1}) \in F'$,
– assume that ρ' contains an infinite branch $x_0, x_1, \ldots$ ultimately state-labelled in $Q \backslash R$: $\exists q \in Q \backslash R$, $\exists N > 0$, $\forall i \geq N$, $\sigma(x_i) = q$. Since $\mathcal{A}$ is progressing, from proposition 10 we know that ρ' is loop-free (which implies that ρ is loop-free) and u is infinite. Since $X_0, X_1, \ldots$ is accepting, $\exists k \geq \nu(x_N)$ such that $(X_{k-1}, X_k, X_{k+1}, \alpha_k) \in T'_q$. ρ' is loop-free so ν is necessarily strictly increasing on $x_N, x_{N+1}, \ldots$, and there exists $j \geq N$ such that $\lambda(x_j) = (q, k)$ and $\lambda(x_{j+1}) = (q, k+1)$. But since $\sigma(x_j) = q$ and $(X_{k-1}, X_k, X_{k+1}, \alpha_k) \in T'_q$

we chose $E((q,k))$ in ρ such that $(q,k{+}1) \notin E((q,k))$. This is a contradiction, and hence ρ' cannot contain such a branch. □

It is quite easy to see that $\mathcal{G}^1_{\mathcal{A}}$ is still too big to be used in an efficient implementation. It contains many useless states, and keeping only the accessible states would not be enough since the initial states are too numerous already. We introduced $\mathcal{G}^1_{\mathcal{A}}$ merely to prove more easily that our construction is correct.

The intuition how to get a smaller GBA from a 2VWAA is as follows: by removing useless parts of runs of a 2VWAA we obtain *minimal runs*, such that removing any subtree of the forest makes the run invalid. Ideally, we would like to construct a GBA $\mathcal{G}^2_{\mathcal{A}}$ which is the restriction of $\mathcal{G}^1_{\mathcal{A}}$ to transitions of the form $(\sigma(\nu^{-1}(i-1)), \sigma(\nu^{-1}(i)), \sigma(\nu^{-1}(i+1)), u_i)$ obtained from minimal runs.

For this, we start from a small set of initial states, and we compute the states and transitions accessible from these states. We need to store both the current set of states Y and the previous one X. Since $\mathcal{A}$ is two-way, it may happen that the set X is not big enough to fulfil all requirements imposed by Y. In this case, we have to backtrack and enlarge X.

Definition 23 ($\mathcal{A}$ to $\mathcal{G}^2_{\mathcal{A}}$). *For any progressing 2VWAA $\mathcal{A} = (Q, \Sigma, \delta, I, F, R)$, let $\mathcal{G}^2_{\mathcal{A}} = (Q'', \Sigma, T'', I'', F'', \mathcal{T}'')$ be the GBA computed by:*

Initialization: $I'' = \{F\} \times I$, $\nabla = \{F\} \times I$, $T'' = \emptyset$.
Then, we apply the following saturation procedure for each state $(X,Y) \in \nabla$ until we reach a fixed point:

```
for each (X', α, Z) ∈ ⨂_{q∈Y} δ(q)
    if X' ⊆ X
(a)     if (Y, Z) ∉ ∇ then add (Y, Z) to ∇
        if (X, Y, Z, α) ∉ T'' then add (X, Y, Z, α) to T''
    else
        for each (F, X, Y, β) ∈ T'' with (F, X) ∈ I''
(b)         if (F, X ∪ X') ∉ ∇ then add (F, X ∪ X') to ∇
            add (F, X ∪ X') to I''
        for each (V, W, X, γ), (W, X, Y, β) ∈ T''
(c)         if (W, X ∪ X') ∉ ∇ then add (W, X ∪ X') to ∇
            if (V, W, X ∪ X', γ) ∉ T'' then add (V, W, X ∪ X', γ) to T''
```

Finally, we set $Q'' = \{X \in 2^Q \mid \exists Y \in 2^Q,\ (X,Y) \in \nabla \text{ or } (Y,X) \in \nabla\}$
$F'' = (2^Q \times 2^F) \cap (Q'' \times Q'')$, *and* $\mathcal{T}'' = \{T''_q \mid q \in Q \backslash R\}$ *where*
$T''_q = \{(\overleftarrow{X}, X, \overrightarrow{X}, \alpha) \in T'' \mid q \notin X$ *or*
$\exists (\overleftarrow{Y}, \beta, \overrightarrow{Y}) \in \delta(q)$ *with* $\overleftarrow{Y} \subseteq \overleftarrow{X}$, $\overrightarrow{Y} \subseteq \overrightarrow{X}$, $\beta \supseteq \alpha$ *and* $q \notin \overrightarrow{Y}\}$

Proposition 24. *For any progressing 2VWAA $\mathcal{A}$, $\mathcal{L}(\mathcal{G}^2_{\mathcal{A}}) \subseteq \mathcal{L}(\mathcal{G}^1_{\mathcal{A}})$.*

Proof. It is easy to notice that any state or transition of $\mathcal{G}^2_{\mathcal{A}}$ appears in $\mathcal{G}^1_{\mathcal{A}}$: $Q'' \subseteq Q'$ and $T'' \subseteq T'$. Hence any accepting run of $\mathcal{G}^2_{\mathcal{A}}$ on a word u is also an accepting run of $\mathcal{G}^1_{\mathcal{A}}$ on the same word. □

Proposition 25. *For any progressing 2VWAA $\mathcal{A}$, $\mathcal{L}(\mathcal{A}) \subseteq \mathcal{L}(\mathcal{G}^2_{\mathcal{A}})$.*

Proof. Let $\rho = (V, E, \sigma, \nu)$ be an accepting run of $\mathcal{A}$ on a word u. We build by induction on k a sequence $\rho'_k = X_0, (X_i, \alpha_i)_{0<i<n}, X_n$ such that:

- $1 \leq n \leq |u| + 1$,
- $(X_0, X_1) \in I''$,
- $\forall 1 \leq i \leq n$, $X_i \subseteq \sigma(\nu^{-1}(i))$ and $(X_{i-1}, X_i) \in \nabla$,
- $\forall 1 \leq i < n$, $u_i \in \alpha_i$ and $(X_{i-1}, X_i, X_{i+1}, \alpha_i) \in T''$,
- $\forall 1 \leq i < n$, $\forall q \in X_i \backslash R$, if $\exists x \in \nu^{-1}(i)$ with $\sigma(x) = q$ and $q \notin \sigma(\overrightarrow{E}(x))$ then $(X_{i-1}, X_i, X_{i+1}, \alpha_i) \in T''_q$.

Let us start with $\rho'_0 = X_0, X_1$ with $X_0 = F$ and $X_1 = \sigma(\Gamma)$ where Γ are the roots of ρ. Since $X_1 \in I$ then $(X_0, X_1) \in I'' \subseteq \nabla$, the inductive hypothesis is satisfied.

Now suppose we have built a sequence $\rho'_k = X_0, (X_i, \alpha_i)_{0<i<n}, X_n$ for some $1 \leq n \leq |u|$, satisfying the inductive hypothesis. If $n = |u| + 1$ we stop the construction.

Otherwise, $\forall q \in X_n$, choose $x_q \in V$ such that $\lambda(x_q) = (q, n)$, and such that if $q \notin R$ then $q \notin \sigma(\overrightarrow{E}(x_q))$ whenever this is possible. Let $X = \{x_q \mid q \in X_n\}$, $X'_{n-1} = \sigma(\overleftarrow{E}(X))$, $X_{n+1} = \sigma(\overrightarrow{E}(X))$. Since ρ is a run of $\mathcal{A}$ on u and $n \leq |u|$, $\exists \alpha_n$ with $u_n \in \alpha_n$ such that $(X'_{n-1}, \alpha_n, X_{n+1}) \in \bigotimes_{q \in X_n} \delta(q)$.

Since ρ'_k satisfies the inductive hypothesis, we have $(X_{n-1}, X_n) \in \nabla$ and three cases can occur:

(a) if $X'_{n-1} \subseteq X_{n-1}$, then from the construction of $\mathcal{G}^2_{\mathcal{A}}$, $(X_n, X_{n+1}) \in \nabla$ and $(X_{n-1}, X_n, X_{n+1}, \alpha_n) \in T''$. Moreover, for each $q \in X_n \setminus R$, if $\exists x \in \nu^{-1}(n)$ with $\sigma(x) = q$ and $q \notin \sigma(\overrightarrow{E}(x))$ then $\exists \beta \supseteq \alpha_n$, $\exists X' \subseteq X_{n-1}$, $\exists Z' \subseteq X_{n+1} \backslash \{q\}$, $(X', \beta, Z') \in \delta(q)$ hence $(X_{n-1}, X_n, X_{n+1}, \alpha_n) \in T''_q$. Therefore, $\rho'_{k+1} = \rho'_k, \alpha_n, X_{n+1}$ satisfies the inductive hypothesis.

We now suppose that $X'_{n-1} \not\subseteq X_{n-1}$. Note that this implies $n \geq 2$, because if $n = 1$ then since ρ is accepting, $X'_0 \subseteq F = X_0$.

(b) If $n = 2$ then $(X_0, X_1, X_2, \alpha_1) \in T''$ and $(X_0, X_1) \in I''$ so from the construction of $\mathcal{G}^2_{\mathcal{A}}$, $(X_0, X_1 \cup X'_1) \in I'' \subseteq \nabla$. Hence $\rho'_{k+1} = X_0, X_1 \cup X'_1$ satisfies the inductive hypothesis.

(c) Assume now that $n \geq 3$. Then we have $(X_{n-3}, X_{n-2}, X_{n-1}, \alpha_{n-2}) \in T''$ and $(X_{n-2}, X_{n-1}, X_n, \alpha_{n-1}) \in T''$. From the construction of $\mathcal{G}^2_{\mathcal{A}}$, $(X_{n-3}, X_{n-2}, X_{n-1} \cup X'_{n-1}, \alpha_{n-2}) \in T''$ and $(X_{n-2}, X_{n-1} \cup X'_{n-1}) \in \nabla$. Moreover if $(X_{n-3}, X_{n-2}, X_{n-1}, \alpha_{n-2}) \in T''_q$ then $(X_{n-3}, X_{n-2}, X_{n-1} \cup X'_{n-1}, \alpha_{n-2}) \in T''_q$. Therefore, $\rho'_{k+1} = X_0, \ldots, X_{n-2}, \alpha_{n-2}, X_{n-1} \cup X'_{n-1}$ satisfies the inductive hypothesis.

Now, we show that the sequence $(\rho'_k)_{k \geq 0}$ converges. For this, consider the alphabet $A = 2^Q \times 2^\Sigma$ partially ordered by $(X, \alpha) \preccurlyeq (Y, \beta)$ if $X \subseteq Y$. Let us write $\rho'_k = (X_0, \emptyset), (X_i, \alpha_i)_{1 \leq i \leq n}, (X_{n+1}, \emptyset) \in A^*$. The sequence of words $(\rho'_k)_{k \geq 0}$ is strictly increasing for the lexicographic order induced by $\preccurlyeq$. Hence, this sequence is either finite (if the construction terminates) or infinite and converges to an infinite word $\rho' \in A^\omega$ (see lemma 26 below).

If u is finite then the words ρ'_k are of length at most $|u|+2$. Therefore the construction terminates at some step k: let $\rho' = \rho'_k$. Since ρ is accepting, $\sigma(\nu^{-1}(|u|+1)) \subseteq F$ so $(X_{|u|}, X_{|u|+1}) \in F''$. Hence ρ' is an accepting run of $\mathcal{G}^2_{\mathcal{A}}$ on u.

If u is infinite then the sequence $(\rho'_k)_{k\geq 0}$ must be infinite and converges to an infinite word $\rho' \in A^\omega$. Since any prefix of ρ' is also a prefix of ρ_k for some k, ρ' is a run of $\mathcal{G}^2_{\mathcal{A}}$ on u. Suppose that ρ' is not accepting: there exists $q \in Q \backslash R$ such that after a given rank N, all transitions used in ρ' are not in T''_q. Hence $\forall x \in V$ if $\lambda(x) = (q,i)$ with $i \geq N$ then $q \in \sigma(\overrightarrow{E}(x))$. Moreover, since $(X_{N-1}, X_N, X_{N+1}, \alpha_N) \notin T''_q$, we have $q \in X_N$. So we can find in ρ an infinite branch ultimately labelled by q, which is a contradiction with ρ accepting. □

Lemma 26. *Let A be a finite set, partially ordered by $\preccurlyeq$. Let $w_0, w_1, ...$ be an infinite sequence of words in A^*. If $(w_i)_{i\geq 0}$ is strictly increasing for the lexicographic order induced by $\preccurlyeq$, then this sequence converges to a limit $w \in A^\omega$.*

Proof. $\forall i \geq 0$, let $w_i = u_i^1 \dots u_i^{n_i}$. $(w_i)_{i\geq 0}$ is increasing for the lexicographic order induced by $\preccurlyeq$, so $(u_i^1)_{i>0}$ is non-decreasing for $\preccurlyeq$. Since A is finite, it reaches a limit u^1 at some $i = i^1$. Now for $i \geq i^1$, $u_i^1 = u^1$ so necessarily $(u_i^2)_{i>i^1}$ is non-decreasing, and reaches a limit u^2 at some $i = i^2$. Going on this way, we clearly build a word $w = u^1 u^2 \dots \in A^\omega$, and this word is the limit of the sequence $(w_i)_{i\geq 0}$. □

As a consequence of Propositions 22, 24 and 25 we obtain:

Theorem 27 (progressing 2VWAA to GBA). *For any progressing 2VWAA $\mathcal{A}$, $\mathcal{L}(\mathcal{G}^1_{\mathcal{A}}) = \mathcal{L}(\mathcal{G}^2_{\mathcal{A}}) = \mathcal{L}(\mathcal{A})$. Hence from any progressing 2VWAA with n states and r repeated states we can construct a GBA accepting the same language with at most 2^n states and $n - r$ acceptance tables.*

We conclude this section by explaining several simplifications that are used in the implementation of the algorithm described in Definition 23.

Saturation procedure: In order to generate all needed transitions, we have to repeat the saturation procedure until no more changes occur. This has to be carefully implemented to avoid redundant computations. The idea here is to timestamp states and transitions by integers. When they are first created, new elements of ∇ are timestamped by 0, whereas new transitions in T'' get the current timestamp. Each time a pair (X, Y) is considered for saturation, the current timestamp is incremented, and when this pair has been treated, it gets the current timestamp. Now, step `(a)` is executed only when the timestamp of (X, Y) is 0. In step `(b)` we consider only transitions (F, X, Y, β) whose timestamps are greater or equal to that of (X, Y). Similarly, in step `(c)`, we only consider pairs of transitions for which at least one timestamp is greater or equal to that of (X, Y).

Transition simplification: The idea here is to remove redundant transitions. When there exist two transitions (X, Y, Z, α) and (X, Y, Z, β) with $\alpha \subseteq \beta$, the first transition is more restrictive than the second one, and thus can be deleted.

This simplification can be done *on-the-fly*, that is when the algorithm adds a new transition to T''.

State simplification: The idea here is to merge equivalent pairs of states. When two pairs of states (X, Y) and (X', Y') have the same outgoing transitions ($(X, Y, Z, \alpha) \in T'' \iff (X', Y', Z, \alpha) \in T''$ and $\forall q \in Q \backslash R$, $(X, Y, Z, \alpha) \in T''_q \iff (X', Y', Z, \alpha) \in T''_q$), they can be merged, and any transition pointing on one of the two states can now point on the merged state.

The overall simplification alternates transition simplification and state simplification until a fixed point is reached.

6 Experimental results

We have implemented two algorithms, building respectively $\mathcal{G}^1_\mathcal{A}$ and $\mathcal{G}^2_\mathcal{A}$ from a PLTL formula φ. Here are the results of some computations on the formula $\varphi_n = \neg\,\mathsf{G}(p_1 \rightarrow \mathsf{F}^{-1}(p_2 \wedge \mathsf{F}^{-1}(p_3 \wedge \ldots \mathsf{F}^{-1}\, p_n)\ldots)$, stating that each p_1 is preceded by p_2, preceded itself by p_3, and so on until p_n. This demonstrates the striking improvement of the on-the-fly algorithm.

	$\mathcal{A}_\varphi$	$\mathcal{G}^1_\mathcal{A}$				$\mathcal{G}^2_\mathcal{A}$			
	states	before	after	time	space	before	after	time	space
φ_2	3	28, 82	6, 11	0.03	<380	7, 10	4, 6	0.01	<380
φ_3	4	100, 544	12, 36	0.83	<380	10, 19	6,13	0.01	<380
φ_4	5	364, 3630	27,102	230	1,700	13, 31	8,23	0.08	635
φ_5	6	1348,24830	58,264	130,000	39,000	16, 46	10,36	9.40	32,000

In order of appearance : tested formula, number of states of the VWAA, and for each $i \in \{1, 2\}$, number of states and transitions of $\mathcal{G}^i_\mathcal{A}$ *before* and *after* simplification, computation time in seconds, memory used in KB.

7 Model-checking

At this point we are able from any PLTL formula φ to compute a GBA accepting the models of φ. In order to apply usual model checking techniques we can transform our GBA to a classical Büchi automaton (BA).

Definition 28 ($\mathcal{G}$ to $\mathcal{B}_\mathcal{G}$). *For any GBA $\mathcal{G} = (Q, \Sigma, T, I, F, \{T_1, \ldots, T_r\})$, let $\mathcal{B}_\mathcal{G} = (Q', \Sigma, T', I', F', R)$ be the BA defined by:*

- $Q' = Q \times Q \times \{0, \ldots, r\}$,
- $T' = \{((q_-, q, j), \alpha, (q, q_+, \mathtt{next}(j, (q_-, q, q_+, \alpha)))) \mid (q_-, q, q_+, \alpha) \in T\}$ *where* $\mathtt{next}(j, t) = \begin{cases} \max\{j \leq i \leq r \mid \forall j < k \leq i,\ t \in T_k\} & \text{if } j \neq r \\ \max\{0 \leq i \leq r \mid \forall 0 < k \leq i,\ t \in T_k\} & \text{if } j = r \end{cases}$
- $I' = I \times \{0\}$,
- $F' = F \times \{0, \ldots, r\}$,
- $R = Q \times Q \times \{r\}$.

Theorem 29 (GBA to BA). *For any GBA $\mathcal{G}$, $\mathcal{L}(\mathcal{B}_\mathcal{G}) = \mathcal{L}(\mathcal{G})$. Hence from any GBA with n states and r acceptance tables we can construct a BA with at most $n^2 \times (r+1)$ states accepting the same language.*

Proof. Let $\sigma = q_0, q_1, \alpha_1, q_2, \alpha_2, \ldots$ be an accepting run of $\mathcal{G}$ on a word $u = u_1 u_2 \ldots$. Let $j_1 = 0$ and $\forall k \geq 0$, $j_{k+1} = \texttt{next}(j_k, (q_{k-1}, q_k, q_{k+1}, \alpha_k))$. It is easy to see that $\sigma' = (q_k, q_{k+1}, j_{k+1})_{k\geq 0}$ is a run of $\mathcal{B}$ on u. If u is finite, $(q_{|u|}, q_{|u|+1}) \in F$ so $(q_{|u|}, q_{|u|+1}, j_{|u|+1}) \in F'$. Otherwise, $\forall k \geq 0$, if $j_k \neq r$ then, since σ is accepting, $\exists k' > k$ such that $(q_{k-1}, q_k, q_{k+1}, \alpha_k) \in T_{j_k+1}$. Hence $\forall k \geq 0$, if $j_k \neq r$ then $\exists k' > k$ such that $j'_k > j_k$ and necessarily there are infinitely many k's such that $j_k = r$: σ' is accepting.

Let $\sigma' = (q_k, q_{k+1}, j_{k+1})_{k\geq 0}$ be an accepting run of $\mathcal{B}$ on a word $u = u_1 u_2 \ldots$. For all $k \geq 1$, we have $((q_{k-1}, q_k, j_k), \alpha_k, (q_k, q_{k+1}, j_{k+1})) \in T'$ for some α_k such that $u_k \in \alpha_k$. Let $\sigma = q_0, q_1, \alpha_1, q_2, \alpha_2, \ldots$: σ is a run of $\mathcal{G}$ on u. Moreover, if u is finite then σ is clearly accepting. Now, if u is infinite, there are infinitely many k's such that $j_k = r$, since σ' is accepting. Thus, for all $0 \leq i \leq r$ and $N > 0$, we find $k \geq N$ such that ($j_k < i$ or $j_k = r$) and $j_{k+1} \geq i$. By definition of `next`, the transition $(q_{k-1}, q_k, q_{k+1}, \alpha_k)$ is in T_i. Hence σ is accepting. □

The drawback of transforming the GBA to a BA is that the number of states and transitions are multiplied by the number of acceptance tables. A better possibility is to compute the product of the system under check and the automaton $\mathcal{G}$ and to use Tarjan's algorithm to compute strongly connected components and check emptiness. Our GBA are easily amenable to this technique and we get a model checking algorithm which is linear in the size of the GBA $\mathcal{G}$ avoiding the costly transformation to a BA.

Definition 30. *Given a GBA $\mathcal{G} = (Q, \Sigma, T, I, F, \mathcal{T})$ and a Kripke structure $(S, \lambda, \rightarrow, I')$ where $\lambda : S \rightarrow \Sigma$, we define the following GBA $(Q'', T'', I'', F'', \mathcal{T}'')$, where:*

- *$Q'' = Q^2 \times (S \cup \{f\})$ where $f \notin S$,*
- *we add a new transition $s \rightarrow f$ for each $s \in S$ such that $\forall s' \in S$, $s \not\rightarrow s'$,*
- *$T'' = \{((q_-, q, s), (q, q_+, s')) \mid s \rightarrow s', \exists \alpha \in 2^\Sigma, \lambda(s) \in \alpha, (q_-, q, q_+, \alpha) \in T\}$,*
- *$I'' = I \times I'$,*
- *$F'' = F \times \{f\}$,*
- *if $\mathcal{T} = \{T_1, \ldots, T_r\}$ then $\mathcal{T}'' = \{T''_1, \ldots, T''_r\}$ where $\forall 1 \leq j \leq r$, $T''_j = \{((q_-, q, s), (q, q_+, s')) \mid s \rightarrow s', \exists \alpha \in 2^\Sigma, \lambda(s) \in \alpha, (q_-, q, q_+, \alpha) \in T_j\}$.*

Theorem 31. *The emptiness for a GBA with n states and r acceptance tables can be decided in linear times w.r.t. the size of this automaton: $\mathcal{O}(n^2 \times r)$ in the worst case.*

Proof. The algorithm to test a GBA $\mathcal{B} = (Q, T, I, F, \mathcal{T})$ for emptiness is quite simple: for inifinite accepting paths, we compute its strongly connected components, and $\mathcal{B}$ has an infinite accepting path if and only if the automaton $\mathcal{B}$ has an accessible strongly connected component where we can find at least one transition from each T_i, $1 \leq i \leq r$.

Using Tarjan's algorithm, accessible strongly connected components of $\mathcal{B}$ can be computed in $\mathcal{O}(|T|)$, hence in linear time w.r.t. the size of $\mathcal{B}$. At the end of this algorithm, each state has a field indicating to which component it belongs. Afterwards, checking if an accessible component has one transition in each T_i can be done in linear time as well: simply go through all the transitions in each T_i, and if a transition's start and arrival state belong to the same component, add i to the list of acceptance tables satisfied by this component. At the end of the algorithm, test if one of the accessible components satisfies all the transition tables.

On the other hand, $\mathcal{B}$ has a finite accepting path if and only if a state in F is accessible. This can be checked in linear time w.r.t. the size of $\mathcal{B}$ again. □

References

1. E.A. Emerson. Temporal and modal logic. In J. van Leeuwen, editor, *Handbook of Theoretical Computer Science*, volume B, chapter 16, pages 995–1072. Elsevier Science, 1990.
2. D. Gabbay, A. Pnueli, S. Shelah, and J. Stavi. On the temporal analysis of fairness. In *Proc. of PoPL'80*, pages 163–173, Las Vegas, Nev., 1980.
3. P. Gastin and D. Oddoux. Fast ltl to büchi automata translation. In *Proc. of CAV'01*, number 2102 in LNCS, pages 53–65. Springer Verlag, 2001.
4. R. Gerth, D. Peled, M.Y. Vardi, and P. Wolper. Simple on-the-fly automatic verification of linear temporal logic. In *Protocol Specification Testing and Verification*, pages 3–18, Warsaw, Poland, 1995. Chapman & Hall.
5. J.A.W. Kamp. *Tense Logic and the Theory of Linear Order*. PhD thesis, University of California, Los Angeles, California, 1968.
6. Y. Kesten, Z. Manna, H. McGuire, and A. Pnueli. A decision algorithm for full propositional temporal logic. In *Proc. of CAV'93*, number 697 in LNCS, pages 97–109. Springer Verlag, 1993.
7. O. Kupferman, N. Piterman, and M.Y. Vardi. Extended temporal logic revisited. In *Proc. of CONCUR'01*, number 2154 in LNCS, pages 519–535. Springer Verlag, 2001.
8. F. Laroussinie, N. Markey, and Ph. Schnoebelen. Temporal logic with forgettable past. In *Proc. of LICS'02*, pages 383–392, 2002.
9. F. Laroussinie and Ph. Schnoebelen. A hierarchy of temporal logics with past. *Theoretical Computer Science*, 148:303–324, 1995.
10. O. Lichtenstein, A. Pnueli, and L.D. Zuck. The glory of the past. In *Proc. of the 3rd Workshop on Logics of Programs*, number 193 in LNCS, pages 196–218. Springer Verlag, 1985.
11. Z. Manna and A. Pnueli. *The temporal logic of reactive and concurent systems: Specification*. Springer Verlag, Berlin-Heidelberg-New York, 1992.
12. A. Pnueli. The temporal logic of programs. In *Proc. of FOCS'77*, pages 46–57, 1977.
13. Y.S. Ramakrishna, L.E. Moser, L.K. Dillon, P.M. Melliar-Smith, and G. Kutty. An automata theoretic decision procedure for propositional temporal logic with Since and Until. *Fundamenta Informaticae*, 17:271–282, 1992.
14. A.P. Sistla and E.M. Clarke. The complexity of propositional linear time logic. *Journal of the Association of Computing Machinery*, 32:733–749, 1985.

15. M.Y. Vardi. Reasonning about the past with two-way automata. In *Proc. of ICALP'98*, number 1443 in LNCS, pages 628–641. Springer Verlag, 1998.
16. M.Y. Vardi and P. Wolper. An automata-theoretic approach to automatic program verification. In *Proc. of LICS'86*, pages 332–344, 1986.
17. M.Y. Vardi and P. Wolper. Reasonning about infinite computations. *Information and Computation*, 115:1–37, 1994.