

Introduction to Programming: Lecture 12

K Narayan Kumar

Chennai Mathematical Institute
<http://www.cmi.ac.in/~kumar>

17 Sep 2013

Binary Search Trees

- ▶ The complexity of all the operations depend on the **height** of the tree.

Binary Search Trees

- ▶ The complexity of all the operations depend on the **height** of the tree.
- ▶ In general, a search tree will not be balanced

Binary Search Trees

- ▶ The complexity of all the operations depend on the **height** of the tree.
- ▶ In general, a search tree will not be balanced
- ▶ Inserting values in ascending or descending order results in highly skewed tree



Height-balanced trees

- ▶ Maintain height balanced trees instead of size-balanced trees. **Height** of left subtree and height of right subtree differ by at most one at any node.



Height-balanced trees

- ▶ Maintain height balanced trees instead of size-balanced trees. **Height** of left subtree and height of right subtree differ by at most one at any node.




- ▶ Height is still logarithmic in size [Adelson-Velskii, Landis]
- ▶ Somewhat easier to maintain.

Height Balanced trees ...

- ▶ Use tree rotations to maintain height balance


Height Balanced trees ...

- ▶ Use tree rotations to maintain height balance
- ▶ Example: rotate right



Height Balanced trees ...


- ▶ Use tree rotations to maintain height balance
- ▶ Example: rotate right



- ▶ Useful if t1 has large height.

Height Balanced trees ...


- ▶ Use tree rotations to maintain height balance
- ▶ Example: rotate right



- ▶ Useful if t_1 has large height.
- ▶ `rotateright (Node (Node t1 y t2) x t3) =
Node t1 y (Node t2 x t3)`

Balanced search trees ...


- ▶ Use tree rotations to maintain height balance
- ▶ Example: rotate left



- ▶ Useful if t_3 has large height.

Balanced search trees ...

- ▶ Use tree rotations to maintain height balance
- ▶ Example: rotate left



- ▶ Useful if t_3 has large height.
- ▶ `rotateleft (Node t1 y (Node t2 x t3)) =`
`Node (Node t1 y t2) x t3`

Balanced search trees ...

- ▶ Assume tree is currently balanced
- ▶ Each `inserttree` or `deletetree` operation creates limited imbalance

Balanced search trees ...

- ▶ Assume tree is currently balanced
- ▶ Each `inserttree` or `deletetree` operation creates limited imbalance
- ▶ Fix imbalance using `rebalance` (to be written!)

Balanced search trees ...

- ▶ Assume tree is currently balanced
- ▶ Each `inserttree` or `deletetree` operation creates limited imbalance
- ▶ Fix imbalance using `rebalance` (to be written!)
- ▶ Assuming `rebalance` exists, we can write

```
inserttree :: Ord a => Stree a -> a -> Stree
inserttree Nil x = Node Nil x Nil
inserttree (Node tl y tr) x
  | x == y      = Node tl y tr
  | x < y      = rebalance (Node (inserttree tl x) y
                                tr)
  | otherwise  = rebalance (Node tl y
                                (inserttree tr x))
```

Rebalancing search trees

- ▶ Define `slope (Node t1 x t2) =`
`(height t1) - (height t2)`

Rebalancing search trees

- ▶ Define `slope (Node t1 x t2) =`
 $(\text{height } t1) - (\text{height } t2)$
 - ▶ In a height balanced tree, slope is -1, 0 or 1

Rebalancing search trees

- ▶ Define $\text{slope}(\text{Node } t1 \text{ x } t2) =$
 $(\text{height } t1) - (\text{height } t2)$
 - ▶ In a height balanced tree, slope is -1, 0 or 1
 - ▶ After inserting/deleting, slopes can be -2,-1, 0, 1 or 2.
Violation happens only at nodes visited by the operation.

Rebalancing search trees

- ▶ Define $\text{slope}(\text{Node } t1 \text{ x } t2) =$
 $(\text{height } t1) - (\text{height } t2)$
 - ▶ In a height balanced tree, slope is -1, 0 or 1
 - ▶ After inserting/deleting, slopes can be -2,-1, 0, 1 or 2.
Violation happens only at nodes visited by the operation.
- ▶ We need to rebalance nodes whose slopes are -2 or 2
(and further assume that the sub-trees below are balanced)

Rebalancing search trees


- ▶ Define $\text{slope}(\text{Node } t1 \text{ x } t2) =$
 $(\text{height } t1) - (\text{height } t2)$
 - ▶ In a height balanced tree, slope is -1, 0 or 1
 - ▶ After inserting/deleting, slopes can be -2,-1, 0, 1 or 2.
Violation happens only at nodes visited by the operation.
- ▶ We need to rebalance nodes whose slopes are -2 or 2
(and further assume that the sub-trees below are balanced)
- ▶ We consider the case where slope is 2
 - ▶ Slope -2 is symmetric

Rebalancing a node with slope 2

- ▶ Two cases
 - ▶ Slope at root of left subtree is 0 or 1
 - ▶ Slope at root of left subtree is -1


Rebalancing a node with slope 2

- ▶ Two cases
 - ▶ Slope at root of left subtree is 0 or 1
 - ▶ Slope at root of left subtree is -1
- ▶ Case 1:



Rebalancing a node with slope 2

- ▶ Two cases
 - ▶ Slope at root of left subtree is 0 or 1
 - ▶ Slope at root of left subtree is -1
- ▶ Case 1: Rotate right




Rebalancing a node with slope 2 ...

- ▶ Case 2: Slope at root of left subtree is -1


Rebalancing a node with slope 2 ...

- ▶ Case 2: Slope at root of left subtree is -1




Rebalancing a node with slope 2 ...

- ▶ Case 2: Slope at root of left subtree is -1
 - ▶ Expand t_2




Rebalancing a node with slope 2 ...

- ▶ Case 2: Slope at root of left subtree is -1
 - ▶ Expand t_2
 - ▶ Rotate left at y —note that z may now be unbalanced



Rebalancing a node with slope 2 ...

- ▶ Case 2: Slope at root of left subtree is -1
 - ▶ Expand t_2
 - ▶ Rotate left at y —note that z may now be unbalanced
 - ▶ Right rotate at x —now z must be balanced



The `rebalance` function

```
rebalance :: Ord a => Stree a -> Stree a
rebalance (Node t1 y t2)
  | abs (sy) < 2          = Node t1 y t2
-- Slope = 2
  | sy == 2 && st1 /= -1 = rotateright (Node t1 y t2)
  | sy == 2 && st1 == -1 =
      rotateright (Node (rotateleft t1) y t2)
...
where
  sy = slope (Node t1 y t2)
  st1 = slope t1
  ...
```

Computing the slope

- ▶ How do we compute `slope`?

Computing the slope

- ▶ How do we compute `slope`?
- ▶ Naively

```
slope :: Tree a -> Int
slope Nil = 0
slope (Node t1 x t2) = (height t1) - (height t2)
```

Computing the slope

- ▶ How do we compute `slope`?
- ▶ Naively

```
slope :: Tree a -> Int
slope Nil = 0
slope (Node t1 x t2) = (height t1) - (height t2)
```

- ▶ To compute `height`, we examine each node in the tree
- ▶ Computing `slope` proportional to size, not height!

Balanced search trees ...

- ▶ Instead, store height at each node
- ▶ Modify definition of `BStree` to add an extra `Int` to record height

```
data Ord a =>  
  BStree a = Nil | Node (BStree a) a Int (BStree a)  
  deriving (Eq,Show)
```

Balanced search trees ...

- ▶ Instead, store height at each node
- ▶ Modify definition of `BStree` to add an extra `Int` to record height

```
data Ord a =>
  BStree a = Nil | Node (BStree a) a Int (BStree a)
  deriving (Eq, Show)
```

- ▶ Now, computing `height` and `slope` takes constant time

```
height Nil = 0
height (Node t1 x m t2) = m
```

```
slope Nil = 0
slope (Node t1 x m t2) = (height t1) - (height t2)
```

Insertion

```
inserttree :: Ord a => BStree a -> a -> BStree a
```

```
inserttree Nil x = Node Nil x 1 Nil
```

```
inserttree (Node tl y h tr) x
```

```
  | x == y    = Node tl y h tr
```

```
  | x < y     = rebalance (Node ntl y nhl tr)
```

```
  | otherwise = rebalance (Node tl y nhr ntr)
```

```
  where
```

```
    ntl = inserttree tl x
```

```
    nhl = 1 + max (height ntl) (height tr)
```

```
    ntr = inserttree tr x
```

```
    nhr = 1 + max (height tl) (height ntr)
```

Deletion

```
deletetree :: Ord a => BStree a -> a -> BStree a
```

```
deletetree Nil x = Nil
```

```
deletetree (Node tl y h tr) x
```

```
  | x < y    = rebalance (Node ntl y nhl tr)
```

```
  | x > y    = rebalance (Node tl y nhr ntr)
```

```
  where
```

```
    ntl = deletetree tl x
```

```
    nhl = 1 + max (height ntl) (height tr)
```

```
    ntr = deletetree tr x
```

```
    nhr = 1 + max (height tl) (height ntr)
```

Cont'd ...

Deletion ...

```
-- In all cases below, we must have x == y
```

```
deletetree (Node Nil y h tr) x = tr
```

```
deletetree (Node tl y h tr) x =  
    rebalance (Node tz z nh tr)
```

```
where
```

```
    (z,tz) = deletemax tl
```

```
    nh = 1 + max (height tz) (height tr)
```

Deletemax

```
deletemax :: Ord a => BStree a -> (a,BStree a)
```

```
deletemax (Node tl y h Nil) = (y,tl)
```

```
deletemax (Node tl y h tr) =  
  (z, rebalance (Node tl y nh tz))  
  where  
    (z,tz) = deletemax tr  
    nh     = 1 + max (height tl) (height tz)
```

Searching

```
searchtree :: Ord a => BStree a -> a -> Bool
```

```
searchtree Nil v = False
```

```
searchtree (Node tl y h tr) v
```

```
  | v == y      = True
```

```
  | v < y      = searchtree tl v
```

```
  | v > y      = searchtree tr v
```

Rebalance:

```
rebalance :: Ord a => Stree a -> Stree a
rebalance (Node t1 y h t2)
  | abs (sy) < 2           = Node t1 y h t2
  | sy == 2 && st1 /= -1 = rotateright (Node t1 y h t2)
  | sy == 2 && st1 == -1 =
      rotateright (Node (rotateleft t1) y nya t2)
...
where
  sy = slope (Node t1 y h t2)
  nya = 1 + max (height t2) (height (rotateleft t1))
  st1 = slope t1
...
```

Rotations

```
rotateright (Node (Node t1 y hy t2) x hx t3) =  
  Node t1 y nhy (Node t2 x nhx t3)  
  where  
    nhx = 1 + max (height t2) (height t3)  
    nhy = 1 + max (height t1) nhx
```

...

Anonymous Functions

- ▶ So far, every Haskell function had a name.

Anonymous Functions

- ▶ So far, every Haskell function had a name.
- ▶ Anonymous functions are functions without names.

Anonymous Functions

- ▶ So far, every Haskell function had a name.
- ▶ Anonymous functions are functions without names.
- ▶ Useful, for instance, if a function is needed just once.

Anonymous Functions

- ▶ So far, every Haskell function had a name.
- ▶ Anonymous functions are functions without names.
- ▶ Useful, for instance, if a function is needed just once.

```
\x -> (head (tail x))
```

Anonymous Functions

- ▶ So far, every Haskell function had a name.
- ▶ Anonymous functions are functions without names.
- ▶ Useful, for instance, if a function is needed just once.

```
\x -> (head (tail x))
```

- ▶ The `\x` is to be read as **lambda x** and comes from **λ -Calculus**.

Anonymous Functions

- ▶ So far, every Haskell function had a name.
- ▶ Anonymous functions are functions without names.
- ▶ Useful, for instance, if a function is needed just once.

```
\x -> (head (tail x))
```

- ▶ The `\x` is to be read as **lambda x** and comes from **λ -Calculus**.
- ▶ Writing ...

```
allseconds = map (\x -> head (tail x))
```

Anonymous Functions

- ▶ So far, every Haskell function had a name.
- ▶ Anonymous functions are functions without names.
- ▶ Useful, for instance, if a function is needed just once.

```
\x -> (head (tail x))
```

- ▶ The `\x` is to be read as **lambda x** and comes from **λ -Calculus**.
- ▶ Writing ...

```
allseconds = map (\x -> head (tail x))
```

... is better than writing

```
allseconds = map second
where
  second x = head (tail x)
```

Functional Composition

- ▶ Composing functions is a natural operation.

```
second x = head (tail x)
```

Functional Composition

- ▶ Composing functions is a natural operation.

```
second x = head (tail x)
```

- ▶ Given $f :: a \rightarrow b$ and $g :: b \rightarrow c$ their composition is defined in Haskell using the `.` operator:

```
g.f :: a -> c  
(g.f) x = g (f x)
```

Functional Composition

- ▶ Composing functions is a natural operation.

```
second x = head (tail x)
```

- ▶ Given $f :: a \rightarrow b$ and $g :: b \rightarrow c$ their composition is defined in Haskell using the `.` operator:

```
g.f :: a -> c  
(g.f) x = g (f x)
```

- ▶ `second = head.tail`

Functional Composition

- ▶ Composing functions is a natural operation.

```
second x = head (tail x)
```

- ▶ Given $f :: a \rightarrow b$ and $g :: b \rightarrow c$ their composition is defined in Haskell using the `.` operator:

```
g.f :: a -> c  
(g.f) x = g (f x)
```

- ▶ `second = head.tail`
- ▶ `.` is a function like any other in Haskell and can be easily defined.

Functional Composition

- ▶ Composing functions is a natural operation.

```
second x = head (tail x)
```

- ▶ Given $f :: a \rightarrow b$ and $g :: b \rightarrow c$ their composition is defined in Haskell using the `.` operator:

```
g.f :: a -> c  
(g.f) x = g (f x)
```

- ▶ `second = head.tail`
- ▶ `.` is a function like any other in Haskell and can be easily defined.
- ▶ What is its type?

Examples

- ▶ Here is a more elaborate example that counts the number of words that begin with a capital letter:

Examples

- ▶ Here is a more elaborate example that counts the number of words that begin with a capital letter:
- ▶ `words :: String -> [String]` returns the words in the given `String`

Examples

- ▶ Here is a more elaborate example that counts the number of words that begin with a capital letter:
- ▶ `words :: String -> [String]` returns the words in the given `String`

```
capcount = length . filter (isUpper.head) . words
```

The `if-then-else` function

- ▶ The `if-then-else` construct works as one expects it to:

The `if-then-else` function

- ▶ The `if-then-else` construct works as one expects it to:

```
if b then e1 else e2
```

If the value of `b`, a boolean expression, is `True` then the value of the expression is `e1` else `e2`

The `if-then-else` function

- ▶ The `if-then-else` construct works as one expects it to:

```
if b then e1 else e2
```

If the value of `b`, a boolean expression, is `True` then the value of the expression is `e1` else `e2`

```
fact n = if (n==0) 1 else (fact (n-1))*n
```

The `let` construct

- ▶ Allows for the introduction of local names much as the `where` command does.

The `let` construct

- ▶ Allows for the introduction of local names much as the `where` command does.

```
let f x = x*x in  
  map f [1,2,3]
```

The `let` construct

- ▶ Allows for the introduction of local names much as the `where` command does.

```
let f x = x*x in  
  map f [1,2,3]
```

- ▶ There are differences between `let` and `where` but we do not discuss them here.