

# Introduction to Programming: Lecture 19

K Narayan Kumar

Chennai Mathematical Institute

<http://www.cmi.ac.in/~kumar>

22 October 2013

## Actions: More details

- ▶ Actions are terms of type  $\mathbf{IO} \ a$  for some  $a$ .

# Actions: More details

- ▶ Actions are terms of type `IO a` for some `a`.
- ▶ Two basic functions used to construct and combine actions are:

```
return :: a -> IO a
```

```
>>= :: IO a -> (a -> IO b) -> IO b
```

# Actions: More details

- ▶ Actions are terms of type `IO a` for some `a`.
- ▶ Two basic functions used to construct and combine actions are:

```
return :: a -> IO a
```

```
>>= :: IO a -> (a -> IO b) -> IO b
```

- ▶ Executing the action `(ac1 >>= ac2)` executes `ac1` unboxes the resulting value, applies `ac2` to get an action and executes that action.

# Actions: More details

- ▶ Actions are terms of type `IO a` for some `a`.
- ▶ Two basic functions used to construct and combine actions are:

```
return :: a -> IO a
```

```
>>= :: IO a -> (a -> IO b) -> IO b
```

- ▶ Executing the action `(ac1 >>= ac2)` executes `ac1` unboxes the resulting value, applies `ac2` to get an action and executes that action.

Actually, `IO` is an example of a `Monad` and these functions are available in any `Monad`.

# Actions: More details

- ▶ Actions are terms of type `IO a` for some `a`.
- ▶ Two basic functions used to construct and combine actions are:

```
return :: a -> IO a
```

```
>>= :: IO a -> (a -> IO b) -> IO b
```

- ▶ Executing the action `(ac1 >>= ac2)` executes `ac1` unboxes the resulting value, applies `ac2` to get an action and executes that action.

Actually, `IO` is an example of a `Monad` and these functions are available in any `Monad`.

- ▶ There are other functions such as `readLn`, `putStrLn`, ... that are specific to certain `IO` types.

# Composing Actions

- ▶ Read a line and print it.

# Composing Actions

- Read a line and print it.

```
getLine >>= putStrLn
```



# Composing Actions

- ▶ Read a line and print it.

```
getLine >>= putStrLn
```

- ▶ What if we want to print the length of the string?

# Composing Actions

- ▶ Read a line and print it.

```
getLine >>= putStrLn
```

- ▶ What if we want to print the length of the string?

```
getLine :: IO String
```

# Composing Actions

- ▶ Read a line and print it.

```
getLine >>= putStrLn
```

- ▶ What if we want to print the length of the string?

```
getLine :: IO String
```

- ▶ That should be coupled with a term of type

```
String -> IO ()
```

 which prints the length of a given string.

# Composing Actions

- ▶ Read a line and print it.

```
getLine >>= putStrLn
```

- ▶ What if we want to print the length of the string?

```
getLine :: IO String
```

- ▶ That should be coupled with a term of type  
`String -> IO ()` which prints the length of a given string.

```
getLine >>= \x -> (putStrLn (show (length x)))
```

# Composing Actions

- ▶ Read a line and print it.

```
getLine >>= putStrLn
```

- ▶ What if we want to print the length of the string?

```
getLine :: IO String
```

- ▶ That should be coupled with a term of type

```
String -> IO ()
```

 which prints the length of a given string.

```
getLine >>= \x -> (putStrLn (show (length x)))
```

- ▶ What if we wanted to print the length two times?

# Composing Actions

- ▶ Read a line and print it.

```
getLine >>= putStrLn
```

- ▶ What if we want to print the length of the string?

```
getLine :: IO String
```

- ▶ That should be coupled with a term of type `String -> IO ()` which prints the length of a given string.

```
getLine >>= \x -> (putStrLn (show (length x)))
```

- ▶ What if we wanted to print the length two times?

```
getLine >>= \x ->
    (putStrLn (show (length x)) >>=
     putStrLn (show (length x)))
```

# Composing Actions

- ▶ Read a line and print it.

```
getLine >>= putStrLn
```

- ▶ What if we want to print the length of the string?

```
getLine :: IO String
```

- ▶ That should be coupled with a term of type `String -> IO ()` which prints the length of a given string.

```
getLine >>= \x -> (putStrLn (show (length x)))
```

- ▶ What if we wanted to print the length two times?

```
getLine >>= \x ->
    (putStrLn (show (length x)) >>=
     putStrLn (show (length x)))
```

- ▶ Alas, that does not type check!

# Composing Actions

- ▶ Read a line and print it.

```
getLine >>= putStrLn
```

- ▶ What if we want to print the length of the string?

```
getLine :: IO String
```

- ▶ That should be coupled with a term of type `String -> IO ()` which prints the length of a given string.

```
getLine >>= \x -> (putStrLn (show (length x)))
```

- ▶ What if we wanted to print the length two times?

```
getLine >>= \x ->
    (putStrLn (show (length x)) >>=
     putStrLn (show (length x)))
```

- ▶ Alas, that does not type check!

```
getLine >>= \x ->
    (putStrLn (show (length x)) >>=
     \y -> putStrLn (show (length x)))
```



# The operator >>

`p >> q = p >>= \n -> q`

# The operator `>>`

`p >> q = p >>= \n -> q`

- ▶ Thus we may rewrite the previous program as

# The operator >>

```
p >> q = p >>= \n -> q
```

- Thus we may rewrite the previous program as

```
getLine >>= \x ->  
    (putStrLn (show (length x)) >>  
     putStrLn (show (length x)))
```

# Translating `do ...` using `>>=`

- ▶ A single actions needs no `do`

`do` `---``>` `exp`  
`exp`

# Translating `do ...` using `>>=`

- ▶ A single actions needs no `do`

`do` `---``>` `exp`  
`exp`

- ▶ No `<-` in the first action,



# Translating `do ...` using `>>=`

- ▶ A single actions needs no `do`

```
do          ---->      exp
  exp
```

- ▶ No `<-` in the first action, any value it returns can be thrown away!

```
do          ---->      exp >> do
  exp                               S
  S
```

- ▶ `name <- exp` is the first action.

# Translating `do ...` using `>>=`

- ▶ A single actions needs no `do`

```
do          --->      exp
  exp
```

- ▶ No `<-` in the first action, any value it returns can be thrown away!

```
do          --->      exp >> do
  exp                      S
  S
```

- ▶ `name <- exp` is the first action. Bind the value returned by the first action to the name `name` and ...

```
do          --->      exp >>=
  name <- exp          \name -> do
  S                      S
```



# Example

```
main = do
    putStrLn ("Please enter your name:")
    name <- getLine
    putStrLn ("Hello " ++ name)
```

# Example

```
main = do
    putStrLn ("Please enter your name:")
    name <- getLine
    putStrLn ("Hello " ++ name)
```

~>

```
main =  putStrLn ("Please enter your name:") >>
        do
            name <- getLine
            putStrLn ("Hello " ++ name)
```

# Example

```
main = do
    putStrLn ("Please enter your name:")
    name <- getLine
    putStrLn ("Hello " ++ name)
```

~>

```
main =  putStrLn ("Please enter your name:") >>
        do
            name <- getLine
            putStrLn ("Hello " ++ name)
```

~>

```
main =  putStrLn ("Please enter your name:") >>
        getLine >=>
            \name ->
                do
                    putStrLn ("Hello " ++ name)
```

~>

## Example ...

```
main =   putStrLn ("Please enter your name:") >>
        getLine >>=
            \name ->
                do
                    putStrLn ("Hello " ++ name)
```

## Example ...

```
main =   putStrLn ("Please enter your name:") >>
         getLine >>=
           \name ->
             do
               putStrLn ("Hello " ++ name)
```

~→

```
main =   putStrLn ("Please enter your name:") >>
         getLine >>=
           \name ->
             putStrLn ("Hello " ++ name)
```

# Reading and Writing into Files

- ▶ To supply input from a file to an executable we can use input redirection

```
$/myprogram < inputfile
```

# Reading and Writing into Files

- ▶ To supply input from a file to an executable we can use input redirection

```
$/myprogram < inputfile
```

- ▶ The output of a program can be saved in a file we can use output redirection

```
$/myprogram > outputfile
```

# Reading and Writing into Files

- ▶ To supply input from a file to an executable we can use input redirection

```
$/myprogram < inputfile
```

- ▶ The output of a program can be saved in a file we can use output redirection

```
$/myprogram > outputfile
```

- ▶ We can redirect input and output together

```
$/myprogram < inputfile > outputfile
```



# Reading and Writing into Files

- ▶ To supply input from a file to an executable we can use input **redirection**

```
$/myprogram < inputfile
```

- ▶ The output of a program can be saved in a file we can use output **redirection**

```
$/myprogram > outputfile
```

- ▶ We can redirect input and output together

```
$/myprogram < inputfile > outputfile
```

- ▶ File input output can also be done directly from within the program.

## File I/O ...

- ▶ To read or write from file, it has to be opened in the appropriate mode.

```
myHandle <- openFile "inputfile" ReadMode
```

# File I/O ...

- ▶ To read or write from file, it has to be opened in the appropriate mode.

```
myHandle <- openFile "inputfile" ReadMode
```

- ▶ The type of `openFile` is

```
FilePath -> IOMode -> IO Handle
```

# File I/O ...

- ▶ To read or write from file, it has to be opened in the appropriate mode.

```
myHandle <- openFile "inputfile" ReadMode
```

- ▶ The type of `openFile` is

```
FilePath -> IOMode -> IO Handle
```

It takes the name of the file, the mode it which it is to be opened, and returns a handle.

# File I/O ...

- ▶ To read or write from file, it has to be opened in the appropriate mode.

```
myHandle <- openFile "inputfile" ReadMode
```

- ▶ The type of `openFile` is

```
FilePath -> IOMode -> IO Handle
```

It takes the name of the file, the mode it which it is to be opened, and returns a handle.

- ▶ The mode can be one of `ReadMode`, `WriteMode`, `AppendMode` and `ReadWriteMode`.

# File I/O ...

- ▶ To read or write from file, it has to be opened in the appropriate mode.

```
myHandle <- openFile "inputfile" ReadMode
```

- ▶ The type of `openFile` is

```
FilePath -> IOMode -> IO Handle
```

It takes the name of the file, the mode it which it is to be opened, and returns a handle.

- ▶ The mode can be one of `ReadMode`, `WriteMode`, `AppendMode` and `ReadWriteMode`.
  - ▶ `WriteMode` begins by creating the file from scratch, deleting anything that is already there.
  - ▶ `AppendMode` appends to the end of an existing file and creating the file if it does not exist.
- ▶ The handle is used in operations pertaining to the opened file.

# File I/O ...

- ▶ To read or write from file, it has to be opened in the appropriate mode.

```
myHandle <- openFile "inputfile" ReadMode
```

- ▶ The type of `openFile` is

```
FilePath -> IOMode -> IO Handle
```

It takes the name of the file, the mode it which it is to be opened, and returns a handle.

- ▶ The mode can be one of `ReadMode`, `WriteMode`, `AppendMode` and `ReadWriteMode`.
  - ▶ `WriteMode` begins by creating the file from scratch, deleting anything that is already there.
  - ▶ `AppendMode` appends to the end of an existing file and creating the file if it does not exist.
- ▶ The handle is used in operations pertaining to the opened file.
- ▶ The function `hClose :: Handle -> IO ()` closes the file.

# File I/O ...

- ▶ To read or write from file, it has to be opened in the appropriate mode.

```
myHandle <- openFile "inputfile" ReadMode
```

- ▶ The type of `openFile` is

```
FilePath -> IOMode -> IO Handle
```

It takes the name of the file, the mode it which it is to be opened, and returns a handle.

- ▶ The mode can be one of `ReadMode`, `WriteMode`, `AppendMode` and `ReadWriteMode`.
  - ▶ `WriteMode` begins by creating the file from scratch, deleting anything that is already there.
  - ▶ `AppendMode` appends to the end of an existing file and creating the file if it does not exist.
- ▶ The handle is used in operations pertaining to the opened file.
- ▶ The function `hClose :: Handle -> IO ()` closes the file.
- ▶ The module `System.IO` has to be imported.



# File I/O

- ▶ Once a file is open we can perform I/O operations using a variety of functions.

# File I/O

- ▶ Once a file is open we can perform I/O operations using a variety of functions.
- ▶ To read a line we can use

```
hGetLine :: Handle -> IO String
```

# File I/O

- ▶ Once a file is open we can perform I/O operations using a variety of functions.
- ▶ To read a line we can use

```
hGetLine :: Handle -> IO String
```

- ▶ Starts from the first position.
- ▶ Each successive call continues reading from the position where the where the previous call ended.

# File I/O

- ▶ Once a file is open we can perform I/O operations using a variety of functions.
- ▶ To read a line we can use

```
hGetLine :: Handle -> IO String
```

- ▶ Starts from the first position.
- ▶ Each successive call continues reading from the position where the where the previous call ended.

and to write to a file we can use

```
hPutStrLn :: Handle -> String -> IO ()
```

# File I/O

- ▶ Once a file is open we can perform I/O operations using a variety of functions.
- ▶ To read a line we can use

```
hGetLine :: Handle -> IO String
```

- ▶ Starts from the first position.
- ▶ Each successive call continues reading from the position where the where the previous call ended.

and to write to a file we can use

```
hPutStrLn :: Handle -> String -> IO ()
```

- ▶ To read other types combine `hGetLine` with the function  
`read :: Read a => String -> a` that works like `readLn`

# File I/O

- ▶ Once a file is open we can perform I/O operations using a variety of functions.
- ▶ To read a line we can use

```
hGetLine :: Handle -> IO String
```

- ▶ Starts from the first position.
- ▶ Each successive call continues reading from the position where the where the previous call ended.

and to write to a file we can use

```
hPutStrLn :: Handle -> String -> IO ()
```

- ▶ To read other types combine `hGetLine` with the function `read :: Read a => String -> a` that works like `readLn`
- ▶ Here is function to read in an `Int` from a line

```
hReadInt h = (hGetLine h) >>=  
              \x -> return ((read :: Int) x)
```

# File I/O – examples

- Copy two lines from the file `FileA` to the file `FileB`

```
copyOneLine :: Handle -> Handle -> IO ()
copyOneLine hi ho = do
    inp  <- hGetLine hi
    hPutStrLn ho inp

main = do
    hinp <- openFile "FileA" ReadMode
    hout <- openFile "FileB" WriteMode
    copyOneLine hinp hout
    copyOneLine hinp hout
    hClose hinp
    hClose hout
```

# Copying Files

- ▶ To copy the entire file, we must know when to stop.



# Copying Files

- ▶ To copy the entire file, we must know when to stop.

The function `hIsEOF :: Handle -> IO Bool` "returns" `True` if the current position has reached the end of the file.

# Copying Files

- To copy the entire file, we must know when to stop.

The function `hIsEOF :: Handle -> IO Bool` "returns" `True` if the current position has reached the end of the file.

- We can copy a files using

```
copyAll :: Handle -> Handle -> IO ()
copyAll hi ho =
    do
        over <- hIsEOF hi
        if over
        then return ()
        else
            do
                copyOneLine hi ho
                copyAll hi ho
```

# The `stdin`, `stdout` and `stderr`

- ▶ The Handle `stdin` is available to read from the **standard input** which is the keyboard unless the input has been redirected.

# The `stdin`, `stdout` and `stderr`

- ▶ The Handle `stdin` is available to read from the **standard input** which is the keyboard unless the input has been redirected.
- ▶ The Handle `stdout` is available to write to the **standard output** which is the screen unless the output has been redirected.

# The `stdin`, `stdout` and `stderr`

- ▶ The Handle `stdin` is available to read from the **standard input** which is the keyboard unless the input has been redirected.
- ▶ The Handle `stdout` is available to write to the **standard output** which is the screen unless the output has been redirected.
- ▶ The Handle `stderr` is available to write to the **standard error**, where error messages are printed, again set to the screen unless explicitly redirected.

# The `stdin`, `stdout` and `stderr`

- ▶ The Handle `stdin` is available to read from the **standard input** which is the keyboard unless the input has been redirected.
- ▶ The Handle `stdout` is available to write to the **standard output** which is the screen unless the output has been redirected.
- ▶ The Handle `stderr` is available to write to the **standard error**, where error messages are printed, again set to the screen unless explicitly redirected.

`copyAll stdin stdout` will act like `echo`

# The `stdin`, `stdout` and `stderr`

- ▶ The Handle `stdin` is available to read from the **standard input** which is the keyboard unless the input has been redirected.
- ▶ The Handle `stdout` is available to write to the **standard output** which is the screen unless the output has been redirected.
- ▶ The Handle `stderr` is available to write to the **standard error**, where error messages are printed, again set to the screen unless explicitly redirected.

`copyAll stdin stdout` will act like `echo`

- ▶ To generate `EOF` from the keyboard use `^D`

# Moving around a file

- ▶ A file is a sequence of **characters**. The positions are numbered starting at 0.



# Moving around a file

- ▶ A file is a sequence of **characters**. The positions are numbered starting at 0.
- ▶ The **Handle** maintains our current position within the file.

# Moving around a file

- ▶ A file is a sequence of **characters**. The positions are numbered starting at 0.
- ▶ The **Handle** maintains our current position within the file.
- ▶ Each time we read or write a character the position increases by 1.

# Moving around a file

- ▶ A file is a sequence of **characters**. The positions are numbered starting at 0.
- ▶ The **Handle** maintains our current position within the file.
- ▶ Each time we read or write a character the position increases by 1.
- ▶ The function **hTell** "returns" the current position.

# Moving around a file

- ▶ A file is a sequence of **characters**. The positions are numbered starting at 0.
- ▶ The **Handle** maintains our current position within the file.
- ▶ Each time we read or write a character the position increases by 1.
- ▶ The function **hTell** "returns" the current position.
- ▶ The function **hSeek** can be used to move to a different position within the file.
  - ▶ Relative to the current position (**RelativeSeek**)
  - ▶ Relative to beginning of the file (**AbsoluteSeek**)
  - ▶ Relative to the end of the file (**SeekFromEnd**)

# Seek and Tell

- ▶ Write at the word "The" at the beginning of the file.

# Seek and Tell

- Write at the word "The" at the beginning of the file.

```
hSeek h AbsoluteSeek 0
```

```
hPutChar h 'T'
```

```
hPutChar h 'h'
```

```
hPutChar h 'e'
```

Assumes that `h` is a handle to a file opened in write or read-write mode.

# Seek and Tell

- ▶ Write at the word "The" at the beginning of the file.

```
hSeek h AbsoluteSeek 0
```

```
hPutChar h 'T'
```

```
hPutChar h 'h'
```

```
hPutChar h 'e'
```

Assumes that `h` is a handle to a file opened in write or read-write mode.

- ▶ Copy the current character to the next position.

# Seek and Tell

- Write at the word "The" at the beginning of the file.

```
hSeek h AbsoluteSeek 0
```

```
hPutChar h 'T'
```

```
hPutChar h 'h'
```

```
hPutChar h 'e'
```

Assumes that `h` is a handle to a file opened in write or read-write mode.

- Copy the current character to the next position.

```
do
```

```
  c <- hGetChar h
```

```
  hPutChar h c
```

Assumes that `h` is a handle opened in read-write mode.



# Seek and Tell

- ▶ Write at the word "The" at the beginning of the file.

```
hSeek h AbsoluteSeek 0
```

```
hPutChar h 'T'
```

```
hPutChar h 'h'
```

```
hPutChar h 'e'
```

Assumes that `h` is a handle to a file opened in write or read-write mode.

- ▶ Copy the current character to the next position.

```
do
```

```
  c <- hGetChar h
```

```
  hPutChar h c
```

Assumes that `h` is a handle opened in read-write mode.

- ▶ Copy the current character to the end of the file.

# Seek and Tell

- ▶ Write at the word "The" at the beginning of the file.

```
hSeek h AbsoluteSeek 0
```

```
hPutChar h 'T'
```

```
hPutChar h 'h'
```

```
hPutChar h 'e'
```

Assumes that `h` is a handle to a file opened in write or read-write mode.

- ▶ Copy the current character to the next position.

```
do
```

```
  c <- hGetChar h
```

```
  hPutChar h c
```

Assumes that `h` is a handle opened in read-write mode.

- ▶ Copy the current character to the end of the file.

```
do
```

```
  c <- hGetChar h
```

```
  hSeek h SeekFromEnd 0
```

```
  hPutChar h c
```

# Files and File I/O

- ▶ Files exist across different runs of a program.  
Any data that needs to be stored across runs has to be in files.

# Files and File I/O

- ▶ Files exist across different runs of a program.  
Any data that needs to be stored across runs has to be in files.
- ▶ Files allow different programs to exchange information.  
One program may write its output to a file from which another reads.

# Files and File I/O

- ▶ Files exist across different runs of a program.  
Any data that needs to be stored across runs has to be in files.
- ▶ Files allow different programs to exchange information.  
One program may write its output to a file from which another reads.
- ▶ Files reside on the disk and can typically store much more data than in memory.  
Large databases are manipulated by programs by loading just parts into the memory.

# Files and File I/O

- ▶ Files exist across different runs of a program.  
Any data that needs to be stored across runs has to be in files.
- ▶ Files allow different programs to exchange information.  
One program may write its output to a file from which another reads.
- ▶ Files reside on the disk and can typically store much more data than in memory.  
Large databases are manipulated by programs by loading just parts into the memory.
- ▶ Files can also be used to exchange data between programs running in different machines.

# Files: Examples

- ▶ A simple Music Library.
  - ▶ Song
  - ▶ Artist
  - ▶ Album
  - ▶ the number of times listed to.

# Files: Examples

- ▶ A simple Music Library.
  - ▶ Song
  - ▶ Artist
  - ▶ Album
  - ▶ the number of times listed to.
- ▶ Each item occupies four **lines**.



# Files: Examples

- ▶ A simple Music Library.
  - ▶ Song
  - ▶ Artist
  - ▶ Album
  - ▶ the number of times listed to.
- ▶ Each item occupies four **lines**.
- ▶ Entries are separated by a blank line.

# Files: Examples

- ▶ A simple Music Library.
  - ▶ Song
  - ▶ Artist
  - ▶ Album
  - ▶ the number of times listened to.
- ▶ Each item occupies four **lines**.
- ▶ Entries are separated by a blank line.
- ▶ Find the song that I have listened to most?

# Files: Examples

- ▶ A simple Music Library.
  - ▶ Song
  - ▶ Artist
  - ▶ Album
  - ▶ the number of times listened to.
- ▶ Each item occupies four **lines**.
- ▶ Entries are separated by a blank line.
- ▶ Find the song that I have listened to most?
- ▶ List the songs in the order of the number of times listened to?

Body and Soul

Django Reinhardt

Djangology Vol 5

4

Entertainer

Scott Joplin

A-Z Encyclopedia of Jazz

10

Romanian Folk Dances for the Piano

Bela Bartok

Concertos for the piano and orchestra Vol 2/3

4

Raag Ek Nishad Ka Behagda

Mallikarjun Mansur

12

...

# Load and process

- Each entry is a four tuple

```
type Entry = (String,String,String,Int)
           deriving (Eq,Ord,Show)
```

```
main = do
```

```
hd <- openFile "MusicData" ReadMode
```

```
el <- fillEList hd []
```

```
---           Process the list el using pure functions
---           Write down el at the end.
```

# Load and process

- ▶ Each entry is a four tuple

```
type Entry = (String,String,String,Int)
           deriving (Eq,Ord,Show)
```

```
main = do
```

```
hd <- openFile "MusicData" ReadMode
```

```
el <- fillEList hd []
```

```
---           Process the list el using pure functions
```

```
---           Write down el at the end.
```

- ▶ Construct a list of entries from the file.

```
fillEList :: Handle -> [Entry] -> IO [Entry]
```

- ▶ Find the song most listened to.

```
most :: [Entry] -> Entry
```

- ▶ Increment its count by 1 (listen to it).

```
incCount :: Entry -> Entry
```

```
...
```

## fillEList...

```
fillEList h l =  
  do  
    over <- hIsEOF h  
    if (over)  
    then  
      return l  
    else  
      do  
        song <- hGetLine h  
        artist <- hGetLine h  
        album <- hGetLine h  
        times <-  
          (hGetLine h >>= (read::Int))  
          hGetLine h  
        nl <- fillEList h l  
        return ((song,artist,album,times):nl)
```

- Populates a list with the contents of the file.

# Records in Haskell : An aside

- ▶ Tuples allow grouping if values.

```
type Entry = (String,String,String,Int)
```



# Records in Haskell : An aside

- ▶ Tuples allow grouping of values.

```
type Entry = (String,String,String,Int)
```

- ▶ We may also use user defined datatypes.

```
data Entry = Entry String String String Int
```

# Records in Haskell : An aside

- ▶ Tuples allow grouping if values.

```
type Entry = (String,String,String,Int)
```

- ▶ We may also use user defined datatypes.

```
data Entry = Entry String String String Int
```

- ▶ In both cases we will need extractor functions to access the components:

```
song  :: Entry -> String  
artist :: Entry -> String  
album :: Entry -> String  
times :: Entry -> Int
```

# Records in Haskell : An aside

- ▶ Tuples allow grouping if values.

```
type Entry = (String,String,String,Int)
```

- ▶ We may also use user defined datatypes.

```
data Entry = Entry String String String Int
```

- ▶ In both cases we will need extractor functions to access the components:

```
song  :: Entry -> String  
artist :: Entry -> String  
album :: Entry -> String  
times :: Entry -> Int
```

- ▶ Haskell allows you define extractor functions simultaneously with the definition of the data type.

# Record Syntax

- We can define `Entry` as follows:

```
data Entry = Entry {  
    song :: String,  
    artist :: String,  
    album :: String,  
    times :: Int  
} deriving (Ord, Eq, Show)
```

# Record Syntax

- ▶ We can define `Entry` as follows:

```
data Entry = Entry {  
    song :: String,  
    artist :: String,  
    album :: String,  
    times :: Int  
} deriving (Ord, Eq, Show)
```

- ▶ This has the effect of

# Record Syntax

- ▶ We can define `Entry` as follows:

```
data Entry = Entry {  
  song :: String,  
  artist :: String,  
  album :: String,  
  times :: Int  
} deriving (Ord, Eq, Show)
```

- ▶ This has the effect of

- ▶ Defining a datatype

```
data Entry = Entry String String String Int
```

# Record Syntax

- ▶ We can define `Entry` as follows:

```
data Entry = Entry {  
  song :: String,  
  artist :: String,  
  album :: String,  
  times :: Int  
} deriving (Ord, Eq, Show)
```

- ▶ This has the effect of
  - ▶ Defining a datatype  
`data Entry = Entry String String String Int`
  - ▶ providing accessor functions `song`, `artist`, `album` and `times`

# Record Syntax

- ▶ We can define `Entry` as follows:

```
data Entry = Entry {  
  song :: String,  
  artist :: String,  
  album :: String,  
  times :: Int  
} deriving (Ord, Eq, Show)
```

- ▶ This has the effect of

- ▶ Defining a datatype

```
data Entry = Entry String String String Int
```

- ▶ providing accessor functions `song`, `artist`, `album` and `times`

- ▶ Values can be created as

```
entry = Entry { song = "Tunji", artist = "John Coltrane",  
               album = "In a Soulful Mood",  
               times = 3 }
```



## Record ...

```
data Entry = Entry {  
    song :: String,  
    artist :: String,  
    album :: String,  
    times :: Int
```

```
entry = Entry { song = "Tunji", artist = "John Coltrane",  
               album = "In a Soulful Mood",  
               times = 3 }
```

## Record ...

```
data Entry = Entry {  
    song :: String,  
    artist :: String,  
    album :: String,  
    times :: Int
```

```
entry = Entry { song = "Tunji", artist = "John Coltrane",  
               album = "In a Soulful Mood",  
               times = 3 }
```

- As expected we have

```
song entry = "Tunji"  
times entry = 3
```

...

# Record ...

- ▶ The order of entries is unimportant if we use the record notation.

# Record ...

- ▶ The order of entries is unimportant if we use the record notation.

```
entry = Entry { song = "Tunji",  
                album = "In a Soulful Mood",  
                artist = "John Coltrane",  
                times = 3 }
```

has the same effect.

# Record ...

- ▶ The order of entries is unimportant if we use the record notation.

```
entry = Entry { song = "Tunji",  
                album = "In a Soulful Mood",  
                artist = "John Coltrane",  
                times = 3 }
```

has the same effect.

- ▶ We are also free to the datatype version.

```
entry = Entry "Tunji" "In a Soulful Mood"  
           "John Coltrane" 3
```

# Back to the Music Album

- ▶ Our current scheme of

# Back to the Music Album

- ▶ Our current scheme of
  - ▶ Load the data from the file to a list

# Back to the Music Album

- ▶ Our current scheme of
  - ▶ Load the data from the file to a list
  - ▶ work with the list



# Back to the Music Album

- ▶ Our current scheme of
  - ▶ Load the data from the file to a list
  - ▶ work with the list
  - ▶ Write the list to the file

# Back to the Music Album

- ▶ Our current scheme of
  - ▶ Load the data from the file to a list
  - ▶ work with the list
  - ▶ Write the list to the file

has some flaws.

# Back to the Music Album

- ▶ Our current scheme of
  - ▶ Load the data from the file to a list
  - ▶ work with the list
  - ▶ Write the list to the file

has some flaws.

- ▶ What if we change only one or two entries?

# Back to the Music Album

- ▶ Our current scheme of
  - ▶ Load the data from the file to a list
  - ▶ work with the list
  - ▶ Write the list to the file

has some flaws.

- ▶ What if we change only one or two entries?  
We still have to write the entire file.

# Back to the Music Album

- ▶ Our current scheme of
  - ▶ Load the data from the file to a list
  - ▶ work with the list
  - ▶ Write the list to the file

has some flaws.

- ▶ What if we change only one or two entries?  
We still have to write the entire file.
- ▶ Can we selectively write only the changed entries?

# Selective Writing

# Selective Writing

- ▶ Seek to the correct position in the file and write.

# Selective Writing

- ▶ Seek to the correct position in the file and write.
- ▶ How do we know the correct position in the file?



# Selective Writing

- ▶ Seek to the correct position in the file and write.
- ▶ How do we know the correct position in the file?
- ▶ Modify `fillELlist` to also record for each entry the position where it begins in the file.

```
type Entry = (String,String,String,Int,Int)
...
```

```
fillElList
...
    do
        pos = hTell h
        song = hGetLine h
        ...
```

# Selective Writing

- ▶ Seek to the correct position in the file and write.
- ▶ How do we know the correct position in the file?
- ▶ Modify `fillELlist` to also record for each entry the position where it begins in the file.

```
type Entry = (String,String,String,Int,Int)
...
```

```
fillEllist
...
    do
        pos = hTell h
        song = hGetLine h
        ...
```

- ▶ To write an entry, seek to its position and then write.

# A Flaw in our idea

- ▶ What happens when the count goes from 9 to 10.

# A Flaw in our idea

- ▶ What happens when the count goes from 9 to 10.
- ▶ We overwrite the first character in the next entry!

# A Flaw in our idea

- ▶ What happens when the count goes from 9 to 10.
- ▶ We overwrite the first character in the next entry!
- ▶ Either write everything from there on.

# A Flaw in our idea

- ▶ What happens when the count goes from 9 to 10.
- ▶ We overwrite the first character in the next entry!
- ▶ Either write everything from there on.
- ▶ or assuming fixed length changable fields.

# A Flaw in our idea

- ▶ What happens when the count goes from 9 to 10.
- ▶ We overwrite the first character in the next entry!
- ▶ Either write everything from there on.
- ▶ or assuming fixed length changable fields.  
Allocate 4 characters for `times` always.